

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020
Version (Revision) : 13.0.0 (12.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Drawing and Stamping Agent. Intended purpose see product description.

Relevant identified uses

Product Categories [PC]

PC25 - PC 25 - Metal working fluids

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co. KG, Industrielack
www.brillux-industrielack.de

Street : Otto-Hahn-Straße 14

Postal code/city : D-59423 Unna

Telephone : +49 2303 8805-0

Telefax : +49 2303 8805-119

Information contact : E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english
Telephone: +49 551 19 24 0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 1 ; H372 - STOT-repeated exposure : Category 1 ; Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Corrosion (GHS05) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020

Version (Revision) : 13.0.0 (12.0.0)

Danger

Hazard components for labelling

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY
2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1

Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H372 Causes damage to organs through prolonged or repeated exposure.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P310 Immediately call a POISON CENTER or a doctor.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY ; REACH registration No. : 01-2119463586-28 ; EC No. : 927-344-2

Weight fraction : $\geq 90 - < 95$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 1 ; H372 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

2-METHYLPROPAN-1-OL ; REACH registration No. : 01-2119484609-23 ; EC No. : 201-148-0 ; CAS No. : 78-83-1

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 STOT SE 3 ; H336

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change contaminated, saturated clothing. When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice.

Following inhalation

Symptom: Headaches, dizzinesses, effect deadening tiredness, muscle weakness, and in exceptions unconsciousness. Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115, mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020
Version (Revision) : 13.0.0 (12.0.0)

Wash immediately with: Water and soap Rub greasy ointment into the skin.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 38,3 °C, shortness of breath, chest congestion or continued coughing or wheezing. No direct artificial respiration to be given by first aider.

Information to physician

Causes central nervous system depression. Dermatitis may result from prolonged or repeated exposure. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal. Call a doctor or poison control center for guidance.

4.2 Most important symptoms and effects, both acute and delayed

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Other signs and symptoms of central nervous system (CNS) depression may include headache, nausea, and lack of coordination. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO₂), water spray.

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide (CO), carbon dioxide (CO₂) and pyrolysis products, toxic.

5.3 Advice for firefighters

Special protective equipment for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Vapour is flammable and heavier than air. Vapour may travel across the ground and reach remote ignition sources, causing a flashback fire danger. The product floats on water and may re-ignite on the surface of water. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8. Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Prevent spread over a wide

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020
Version (Revision) : 13.0.0 (12.0.0)

area (e.g. by containment or oil barriers). Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Avoid: Inhalation of vapours or spray/mists, Skin contact, Eye contact. Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Never use pressure to empty container. Only allow access to authorised staff.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Environmental precautions

Provide for retaining containers, eg. floor pan without outflow.

Advices on general occupational hygiene

Wear personal protection equipment (refer to section 8). When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Floors should be impervious, resistant to liquids and easy to clean. Provide adequate ventilation as well as local exhaust at critical locations. Keep container tightly closed.

Hints on joint storage

Storage class (TRGS 510) : 3

Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place.

Protect against : Heat. Humidity.

7.3 Specific end use(s)

Drawing and Stamping Agent. Intended purpose see product description.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 300 mg/m³

Remark : H

Version :

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020

Version (Revision) : 13.0.0 (12.0.0)

2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 310 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 29.03.2019

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL/DMEL (Industrial) (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 44 mg/kg
Limit value type : DNEL/DMEL (Industrial) (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 330 mg/m³
Limit value type : DNEL/DMEL (Consumer) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Oral
Exposure frequency : Long-term (repeated)
Limit value : 25 mg/kg
Safety factor : 1 Days
Limit value type : DNEL/DMEL (Consumer) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 55 mg/m³
Limit value type : DNEL/DMEL (Industrial) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 310 mg/m³

PNEC

Limit value type : PNEC (Aquatic, freshwater) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Water (Including sewage plant)
Limit value : 0,4 mg/l
Limit value type : PNEC (Aquatic, marine water) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Water (Including sewage plant)
Limit value : 0,04 mg/l
Limit value type : PNEC (Sediment, freshwater) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Soil
Limit value : 1,52 mg/kg
Limit value type : PNEC (Sediment, marine water) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Soil
Limit value : 0,125 mg/kg
Limit value type : PNEC soil (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Soil
Limit value : 0,0699 mg/kg
Limit value type : PNEC (Sewage treatment plant) (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Water (Including sewage plant)
Limit value : 10 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

goggles (EN 166)

Remark

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115, mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020
Version (Revision) : 13.0.0 (12.0.0)

Note DGUV-Rule 112-192.

Skin protection

Hand protection

Use safety gloves according to EN 374. Suitable glove materials: fluoro-rubber, butyl-rubber or nitrile-rubber. Please pay attention to the glove penetration times of the substances named below in chapter 2, according to the glove manufactures.

Remark : After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.

Body protection

Required properties : Antistatic, non-melting.

Recommended material : Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Remark : Note DGUV-Rule 112-189. Note TRGS 401.

Respiratory protection

Respiratory protection necessary at: Insufficient ventilation, insufficient exhaust or spray application. insufficient exhaust

Suitable respiratory protection apparatus

Filter mask with filter type A for short-term work.

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

Occupational exposure controls

Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : According to product identification.

Odour

Like solvent.

Safety relevant basis data

Melting point/melting range :			not applicable
Initial boiling point and boiling range :	(1013 hPa)	approx.	110 - 180 °C
Decomposition temperature :			No data available
Flash point :		>	23 - 60 °C
Ignition temperature :		approx.	270 °C
Lower explosion limit :		approx.	0,6 Vol-%
Upper explosion limit :		approx.	7 Vol-%
Vapour pressure :	(50 °C)	<	50 hPa
Density :	(20 °C)		0,7 - 0,9 g/cm ³
Water solubility :	(20 °C)		Not or little soluble
pH :			No data available
log P O/W :			No data available
Flow time :	(20 °C)	<	13 s
Viscosity :	(23 °C)		No data available
Cinematic viscosity :	(40 °C)	<=	20,5 mm ² /s

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115, mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020
Version (Revision) : 13.0.0 (12.0.0)

Solid content : No data available
Odour threshold : No data available
Relative vapour density : (20 °C) > 1 (air = 1)
Vapourisation rate : No data available
Oxidising liquids : Not oxidising.

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated. Oxidizing agent.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : ATEmix calculated
Exposure route : Oral
Effective dose : not relevant
Parameter : LD50 (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Exposure route : Oral
Species : Rat
Effective dose : > 15000 mg/kg
Parameter : LD50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Oral
Species : Rat
Effective dose : 2830 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : not relevant
Parameter : LD50 (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 3400 mg/kg
Parameter : LD50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Dermal
Species : Rat
Effective dose : 3400 mg/kg
Exposure time : 4 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020

Version (Revision) : 13.0.0 (12.0.0)

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalation (vapour)
Effective dose : not relevant
Parameter : LC50 (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Exposure route : Inhalation
Species : Rat
Effective dose : > 13,1 mg/l
Exposure time : 4 h
Parameter : LC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route : Inhalation
Species : Rat
Effective dose : 8000 ppm

Assessment/classification

Vapours may cause drowsiness and dizziness.

Irritant and corrosive effects

Irritation to respiratory tract

May cause respiratory irritation.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of skin contact

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 10 - 30 mg/l
Exposure time : 96 h
Parameter : LC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Pimephales promelas (fathead minnow)
Effective dose : 1430 mg/l
Exposure time : 96 h

Acute (short-term) daphnia toxicity

Parameter : EC50 (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Species : Daphnia magna (Big water flea)
Effective dose : 10 - 22 mg/l
Exposure time : 48 h
Parameter : EC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Daphnia magna (Big water flea)
Effective dose : 1100 mg/l
Exposure time : 48 h

Chronic (long-term) daphnia toxicity

Parameter : NOEC (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Species : Daphnia magna (Big water flea)
Effective dose : 0,97 mg/l
Exposure time : 21 Days
Parameter : NOEC (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Daphnia magna (Big water flea)
Effective dose : 20 mg/l
Exposure time : 21 Days

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020

Version (Revision) : 13.0.0 (12.0.0)

Acute (short-term) algae toxicity

Parameter : EC50 (NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY)
Species : Pseudokirchneriella subcapitata
Effective dose : 4,6 - 10 mg/l
Exposure time : 72 h
Parameter : EC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Pseudokirchneriella subcapitata
Effective dose : 632 mg/l
Exposure time : 72 h
Parameter : EL50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Pseudokirchneriella subcapitata
Effective dose : 53 mg/l
Exposure time : 72 h

12.2 Persistence and degradability

Biodegradation

Biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

EWC-Code: 14 06 03. Uncleaned packaging: EWC-Code: 15 01 10. Cleaned packaging: EWC-Code: 15 01 04.

Waste treatment options

Appropriate disposal / Package

Completely emptied packages can be recycled.

13.2 Additional information

Note sections 7 and 8.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (ISOBUTYL ALCOHOL)

Sea transport (IMDG)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)
Revision date : 12.03.2020
Print date : 12.03.2020

Version (Revision) : 13.0.0 (12.0.0)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · ISOBUTYL ALCOHOL)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (ISOBUTYL ALCOHOL)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3 / N

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes

Sea transport (IMDG) : Yes (P)

Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National regulations

Water hazard class (WGK)

Class : 2 (Significant hazardous to water) Classification according to AwSV

Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

15. Restrictions on use

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Zieh- und Stanzmittel 5115,
mittelflüchtig, farblos (5115-.0102)

Revision date : 12.03.2020

Print date : 12.03.2020

Version (Revision) : 13.0.0 (12.0.0)

16.2 Abbreviations and acronyms

TRGS: German Technical Rule for Hazardous Substances. BGR(I): Rule (Information) from the German employers liability insurance association. DGUV: German Statutory Accident Insurance. AwSV: Ordinance on plants for the handling of substances hazardous to water. VCI: German chemical industry association. EWC: European Waste Catalogue.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
