

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

Print date : 26.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Waterborne coating. Intended purpose see technical data sheet.

Relevant identified uses

Product Categories [PC]

PC9 - Coatings and paints, fillers, putties, thinners

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co. KG, Industrielack
www.brillux-industrielack.de

Street : Otto-Hahn-Straße 14

Postal code/city : D-59423 Unna

Telephone : +49 (0)2303 8805-0

Telefax : +49 (0)2303 8805-119

Information contact : E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

1.4 Emergency telephone number

Giftnotruf Berlin (poisons centre), consultation in german and english
Telephone: +49 (0)30 30686 790.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

None

Classification according to Directive 67/548/EEC or 1999/45/EC

None

Additional information

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH208 Contains A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Labelling (67/548/EEC or 1999/45/EC)

Special provisions concerning the labelling of certain mixtures

101 Safety data sheet available for professional user on request.

2.3 Other hazards

None

SECTION 3: Composition / information on ingredients

Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) :

7.0.0 (6.0.0)

Print date : 26.11.2015

3.2 Mixtures

Hazardous ingredients

BUTYL CELLOSOLVE ; REACH registration No. : 01-2119475108-36 ; EC No. : 203-905-0; CAS No. : 111-76-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

2-DIMETHYLAMINOETHANOL ; REACH registration No. : 01-2119492298-24 ; EC No. : 203-542-8; CAS No. : 108-01-0

Weight fraction : $< 0,5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 3 ; H331 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 STOT SE 3 ; H335

TRIETHYLAMINE ; REACH registration No. : 01-21194756-467-26 ; EC No. : 204-469-4; CAS No. : 121-44-8

Weight fraction : $< 0,5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Acute Tox. 3 ; H311 Acute Tox. 3 ; H331 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 STOT SE 3 ; H335

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2- METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : 55965-84-9

Weight fraction : $\geq 0,00015 - < 0,0015 \%$

Classification 1272/2008 [CLP] : Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Acute Tox. 3 ; H331 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change contaminated, saturated clothing. When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash immediately with: Water and soap. Do not wash with: Solvents/Thinner.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO₂), water spray.

Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) :

7.0.0 (6.0.0)

Print date : 26.11.2015

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide (CO), carbon dioxide (CO₂) and pyrolysis products, toxic.

5.3 Advice for firefighters

Special protective equipment for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Avoid: Inhalation of vapours or spray/mists. Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Never use pressure to empty container. Only allow access to authorised staff.

Measures to prevent fire

Keep away from sources of ignition. - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advices on general occupational hygiene

Wear personal protection equipment (refer to section 8). When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Floors should be impervious, resistant to liquids and easy to clean. Keep container tightly closed.

Hints on joint storage

Storage class (TRGS 510) : 10

Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place.

Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

Print date : 26.11.2015

Protect against : Heat, frost and humidity.

7.3 Specific end use(s)

Waterborne coating. Intended purpose see technical data sheet.

Industrial sector specific solutions

Note DGUV-Rule 100-500, section 2.29 (processing coating materials). Note DGUV-Rule 109-013.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 20 ppm / 98 mg/m³
Peak limitation : 4(II)
Remark : H,Y
Version : 02.04.2014

Limit value type (country of origin) : STEL (EC)
Limit value : 50 ppm / 246 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 98 mg/m³
Remark : H
Version : 08.06.2000

TRIETHYLAMINE ; CAS No. : 121-44-8

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1 ppm / 4,2 mg/m³
Peak limitation : 2(I)
Remark : H
Version : 02.04.2014

Limit value type (country of origin) : STEL (EC)
Limit value : 3 ppm / 12,6 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 2 ppm / 8,4 mg/m³
Remark : H
Version : 08.06.2000

Biological limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts
Limit value : 100 mg/l
Version : 31.03.2004

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL/DMEL (Industrial) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : 89 mg/kg
Limit value type : DNEL/DMEL (Industrial) (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) :

7.0.0 (6.0.0)

Print date : 26.11.2015

Exposure frequency : Long-term (repeated)
Limit value : 1,04 mg/kg
Limit value type : DNEL/DMEL (Industrial) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 663 mg/m³
Limit value type : DNEL/DMEL (Industrial) (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 7,4 mg/m³
Limit value type : DNEL/DMEL (Industrial) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 75 mg/kg
Limit value type : DNEL/DMEL (Industrial) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 98 mg/m³

PNEC

Limit value type : PNEC (Industrial) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Water (Including sewage plant)
Limit value : 8,8 mg/l
Limit value type : PNEC (Industrial) (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Water (Including sewage plant)
Exposure time : Long-term (continuous)
Limit value : 0,0661 mg/l
Limit value type : PNEC (Industrial) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Soil
Limit value : 2,8 mg/kg
Limit value type : PNEC (Industrial) (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Soil
Limit value : 0,0177 mg/kg

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

goggles (EN 166)

Remark

Note DGUV-Rule 112-192.

Skin protection

Hand protection

Use safety gloves according to EN 374. Suitable glove materials: fluoro-rubber, butyl-rubber or nitrile-rubber. Please pay attention to the glove penetration times of the substances named below in chapter 2, according to the glove manufactures.

Remark : After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.

Body protection

Required properties : Antistatic, non-melting.

Recommended material : Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Remark : Note DGUV-Rule 112-189. Note TRGS 401.

Respiratory protection

Respiratory protection necessary at: Insufficient ventilation, insufficient exhaust or spray application.

Suitable respiratory protection apparatus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)
Revision date : 26.11.2015
Print date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

Combination filter mask A2-P2 for short-term work.
European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

Occupational exposure controls

Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : liquid

Colour : According to product identification.

Odour

product specific, characteristic.

Safety relevant basis data

Melting point/melting range :			not applicable
Initial boiling point and boiling range :	(1013 hPa)	>	100 °C
Decomposition temperature :			No data available
Flash point :		>	65 °C
Ignition temperature :			No data available
Lower explosion limit :		ca.	1,1 Vol-%
Upper explosion limit :		ca.	10 Vol-%
Vapour pressure :	(50 °C)	<	150 hPa
Density :	(20 °C)		1 - 1,5 g/cm ³
Water solubility :	(20 °C)		consolute miscible
pH :			8 - 9
log P O/W :			No data available
Flow time :	(20 °C)		75 - 85 s DIN-cup 4 mm
Viscosity :	(23 °C)		No data available
Cinematic viscosity :	(40 °C)	>	20,5 mm ² /s
Solid content :			No data available
Odour threshold :			not relevant
Relative vapour density :	(20 °C)		No data available
Vapourisation rate :			No data available
Oxidising liquids :	Not oxidising.		

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No information available.

Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

Print date : 26.11.2015

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated. Oxidising agent.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Oral
Species : Rat
Effective dose : 1183 mg/kg
Method : OECD 401
Parameter : LD50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Oral
Species : Rat
Effective dose : 1480 mg/kg
Parameter : ATE (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Oral
Effective dose : > 300 - <= 2000 mg/kg
Parameter : ATE (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Oral
Effective dose : > 300 - <= 2000 mg/kg
Parameter : ATE (TRIETHYLAMINE ; CAS No. : 121-44-8)
Exposure route : Oral
Effective dose : > 300 - <= 2000 mg/kg
Parameter : ATE (A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : 55965-84-9)
Exposure route : Oral
Effective dose : > 50 - <= 300 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : > 5000 mg/kg
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg
Parameter : LD50 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Dermal
Species : Rabbit
Effective dose : 1219 mg/kg
Method : OECD 402
Parameter : ATE (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Effective dose : > 1000 - <= 2000 mg/kg
Parameter : ATE (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Dermal
Effective dose : > 1000 - <= 2000 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) :

7.0.0 (6.0.0)

Print date : 26.11.2015

Parameter : ATE (TRIETHYLAMINE ; CAS No. : 121-44-8)
Exposure route : Dermal
Effective dose : > 200 - <= 1000 mg/kg
Parameter : ATE (A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2- METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : 55965-84-9)
Exposure route : Dermal
Effective dose : > 200 - <= 1000 mg/kg

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalative (vapour)
Effective dose : > 20 mg/l
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 800 ppm
Exposure time : 8 h
Parameter : LC50 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Exposure route : Inhalation
Species : Rat
Effective dose : 6,1 mg/l
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Mouse
Effective dose : 700 ppm
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 3,9 mg/l
Exposure time : 8 h

Irritant and corrosive effects

Primary irritation to the skin

Parameter : Primary irritation to the skin (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Species : Rabbit
Method : OECD 404

Irritation to eyes

Parameter : Irritation to eyes (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)
Species : Rabbit
Result : Irreversible.
Method : OECD 405

Irritation to respiratory tract

May cause respiratory irritation.

Practical experience/human evidence

The inhalation of dust/mist or aerosols causes irritation of the respiratory tract.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of skin contact

Frequently or prolonged contact with skin may cause dermal irritation.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) :

7.0.0 (6.0.0)

Print date : 26.11.2015

Acute (short-term) fish toxicity

Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)

Species : Oncorhynchus mykiss (Rainbow trout)

Effective dose : 1474 mg/l

Exposure time : 96 h

Parameter : LC50 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)

Species : Leuciscus idus (golden orfe)

Effective dose : 146,6 mg/l

Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)

Species : Brachydanio rerio (zebra-fish)

Effective dose : > 100 mg/l

Exposure time : 21 Days

Acute (short-term) daphnia toxicity

Parameter : EC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)

Species : Daphnia magna (Big water flea)

Effective dose : 1550 mg/l

Exposure time : 48 h

Parameter : EC50 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)

Species : Daphnia magna (Big water flea)

Effective dose : 98,4 mg/l

Exposure time : 48 h

Chronic (long-term) daphnia toxicity

Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)

Species : Daphnia magna (Big water flea)

Effective dose : 100 mg/l

Exposure time : 21 Days

Acute (short-term) algae toxicity

Parameter : EbC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)

Species : Pseudokirchneriella subcapitata

Effective dose : 911 mg/l

Exposure time : 72 h

Parameter : EC50 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)

Species : Scenedesmus subspicatus

Effective dose : 66,1 mg/l

Exposure time : 72 h

Parameter : EC50 (A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : 55965-84-9)

Species : Algae

Evaluation parameter : Anabaena flos-aquae

Effective dose : 0,043 mg/l

Exposure time : 120 h

Bacteria toxicity

Parameter : EC0 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)

Species : Pseudomonas putida

Effective dose : > 700 mg/l

Exposure time : 16 h

Effects in sewage plants

Parameter : EC20 (2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0)

Inoculum : Municipal

Effective dose : > 1000 mg/l

Exposure time : 30 min

Method : OECD 209

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

Print date : 26.11.2015

12.2 Persistence and degradability

Biodegradation

The solvent is biodegradable. In accordance with the required stability the product is poorly biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

EWC-Code: 08 01 11. Uncleaned packaging: EWC-Code: 15 01 10. Cleaned packaging: EWC-Code: 15 01 04.

Waste treatment options

Appropriate disposal / Package

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

Note sections 7 and 8.

SECTION 14: Transport information

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

14.4 Packing group

No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

Print date : 26.11.2015

mixture

EU legislation

Other regulations (EU)

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 0,5 %

Weight fraction (Number 5.2.7. III) : < 1 %

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

Betriebssicherheitsverordnung (BetrSichV)

No flammable liquid according to BetrSichV.

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Special rules for supplemental label elements for certain mixtures

16.2 Abbreviations and acronyms

TRGS: German Technical Rule for Hazardous Substances. BGR(I): Rule (Information) from the german employers liability insurance association. DGUV: German Statutory Accident Insurance. VwVwS: Administrative Regulation on the Classification of Substances Hazardous to Waters. VCI: German chemical industry association. EWC: European Waste Catalogue.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H302	Harmful if swallowed.
H302+H312	Harmful if swallowed or in contact with skin.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H311+H331	Toxic in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.

16.6 Training advice

None

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Hydro-Einbrennlack 5501 (SORTE 5501)
(only valid for plain colors)

Revision date : 26.11.2015

Print date : 26.11.2015

Version (Revision) : 7.0.0 (6.0.0)

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
