

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

2K-PUR-High-Solid-Lack 5732 (SORTE 5732)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Solvent-based coating. Intended purpose see technical data sheet.

#### Relevant identified uses

##### Product Categories [PC]

PC9 - Coatings and paints, fillers, putties, thinners

#### Remark

The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co. KG, Industrielack  
www.brillux-industrielack.de

**Street :** Otto-Hahn-Straße 14

**Postal code/city :** D-59423 Unna

**Telephone :** +49 2303 8805-0

**Telefax :** +49 2303 8805-119

**Information contact :** E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

### 1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english  
Telephone: +49 551 19 24 0

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02)

##### Signal word

Warning

##### Hazard statements

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

P233 Keep container tightly closed.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P403+P235 Store in a well-ventilated place. Keep cool.

### Special rules for supplemental label elements for certain mixtures

EUH208 Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate. May produce an allergic reaction.

### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

N-BUTYL ACETATE ; REACH registration No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

2-METHOXY-1-METHYLETHYL ACETATE ; REACH registration No. : 01-2119475791-29 ; EC No. : 203-603-9; CAS No. : 108-65-6

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226  
Substance with a common (EC) occupational exposure limit value.

5-METHYLHEXAN-2-ONE ; REACH registration No. : 01-2119472300-51 ; EC No. : 203-737-8; CAS No. : 110-12-3

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H332

2-BUTOXYETHYL ACETATE ; REACH registration No. : 01-2119475112-47 ; EC No. : 203-933-3; CAS No. : 112-07-2

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H312 Acute Tox. 4 ; H332

XYLENE ; REACH registration No. : 01-2119488216-32 ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; EC No. : 255-437-1; CAS No. : 41556-26-7

Weight fraction :  $\geq 0,25 - < 0,5$  %  
Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; EC No. : 280-060-4; CAS No. : 82919-37-7

Weight fraction :  $\geq 0,1 - < 0,25$  %  
Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Change contaminated, saturated clothing. When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

## In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

## After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye.

## After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

## 4.2 Most important symptoms and effects, both acute and delayed

No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), water spray.

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and pyrolysis products, toxic.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Use suitable breathing apparatus.

### 5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

### 6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Avoid: Inhalation of vapours or spray/mists Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Never use pressure to empty container. Only allow access to authorised staff.

### Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

### Advices on general occupational hygiene

Wear personal protection equipment (refer to section 8). When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

## 7.2 Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Floors should be impervious, resistant to liquids and easy to clean. Provide adequate ventilation as well as local exhaustion at critical locations. Keep container tightly closed.

### Hints on joint storage

**Storage class (TRGS 510) :** 3

### Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

### Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place.

**Protect against :** Heat. Humidity.

## 7.3 Specific end use(s)

Solvent-based coating. Intended purpose see technical data sheet.

### Industrial sector specific solutions

Note DGUV-Rule 100-500, section 2.29 (processing coating materials). Note DGUV-Rule 109-013.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 62 ppm / 300 mg/m<sup>3</sup>

Peak limitation : 2(I)

Remark : Y

Version : 29.03.2019

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 ppm / 270 mg/m<sup>3</sup>

Peak limitation : 1(I)

Remark : Y

Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )

Limit value : 100 ppm / 550 mg/m<sup>3</sup>

Remark : H

Version : 31.01.2018

Limit value type (country of origin) : TWA ( EC )

Limit value : 50 ppm / 275 mg/m<sup>3</sup>

Remark : H

Version : 31.01.2018

5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3

Limit value type (country of origin) : TRGS 900 ( D )

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

Limit value : 20 ppm / 95 mg/m<sup>3</sup>  
Version : 29.03.2019  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 20 ppm / 95 mg/m<sup>3</sup>  
Version : 31.01.2018  
2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 10 ppm / 65 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : H,Y  
Version : 29.03.2019  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 50 ppm / 333 mg/m<sup>3</sup>  
Remark : H  
Version : 31.01.2018  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 20 ppm / 133 mg/m<sup>3</sup>  
Remark : H  
Version : 31.01.2018  
XYLENE ; CAS No. : 1330-20-7  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 440 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H  
Version : 01.10.1993  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Version :  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Version :

## Biological limit values

2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts  
Limit value : 100 mg/l  
Version : 29.03.2019  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Butoxy acetic acid / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts  
Limit value : 150 mg/g Kr  
Version : 29.03.2019  
XYLENE ; CAS No. : 1330-20-7  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift  
Limit value : 1,5 mg/l  
Remark : 5/2013 DFG  
Version : 01.10.1993  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift  
Limit value : 2 g/l  
Version : 01.10.1993

## DNEL/DMEL and PNEC values

### DNEL/DMEL

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

Limit value type : DNEL Consumer (systemic) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 102,34 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Industrial) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 96 mg/kg

Limit value type : DNEL/DMEL (Industrial) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 48 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Industrial) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 7 mg/kg

Limit value type : DNEL/DMEL (Industrial) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 480 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Consumer) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 54,8 mg/kg

Limit value type : DNEL/DMEL (Consumer) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 33 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Consumer) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Oral  
Exposure frequency : Long-term (repeated)  
Limit value : 1,67 mg/kg

Limit value type : DNEL/DMEL (Industrial) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 275 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Industrial) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 153,5 mg/kg

Limit value type : DNEL/DMEL (Industrial) ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 8 mg/kg  
Safety factor : 1 Days

Limit value type : DNEL/DMEL (Industrial) ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 95 mg/m<sup>3</sup>

Limit value type : DNEL/DMEL (Industrial) ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

Limit value : 818 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 102 mg/kg  
Limit value type : DNEL/DMEL (Industrial) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 289 mg/kg  
Limit value type : DNEL/DMEL (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 133 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Dermal  
Exposure frequency : Short-term (acute)  
Limit value : 102 mg/kg  
Limit value type : DNEL/DMEL (Industrial) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 180 mg/kg  
Limit value type : DNEL/DMEL (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 333 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 77 mg/kg  
Limit value type : DNEL worker (local and systemic) ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 2,5 mg/kg  
Limit value type : DNEL worker (local and systemic) ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 2,35 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local and systemic) ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Exposure route : Dermal  
Exposure frequency : Long-term (repeated)  
Limit value : 2,5 mg/kg  
Limit value type : DNEL worker (local and systemic) ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Exposure route : Inhalation  
Exposure frequency : Long-term (repeated)  
Limit value : 2,35 mg/m<sup>3</sup>

## PNEC

Limit value type : PNEC (Aquatic, freshwater) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Water (Including sewage plant)  
Limit value : 0,18 mg/l  
Limit value type : PNEC (Aquatic, intermittent release) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Water (Including sewage plant)  
Limit value : 0,36 mg/l  
Limit value type : PNEC (Aquatic, marine water) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

---

Exposure route :	Water (Including sewage plant)
Limit value :	0,018 mg/l
Limit value type :	PNEC (Sediment, freshwater) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Soil
Limit value :	0,981 mg/kg
Limit value type :	PNEC (Sediment, marine water) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Soil
Limit value :	0,0981 mg/kg
Limit value type :	PNEC soil ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Soil
Limit value :	0,0903 mg/kg
Limit value type :	PNEC (Sewage treatment plant) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Water (Including sewage plant)
Limit value :	35,6 mg/l
Limit value type :	PNEC (Aquatic, freshwater) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Water (Including sewage plant)
Limit value :	0,635 mg/l
Limit value type :	PNEC (Aquatic, marine water) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Water (Including sewage plant)
Limit value :	0,0635 mg/l
Limit value type :	PNEC (Sediment, freshwater) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Soil
Limit value :	3,29 mg/kg
Limit value type :	PNEC (Sediment, marine water) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Soil
Limit value :	0,329 mg/kg
Limit value type :	PNEC soil ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Soil
Limit value :	29 mg/kg
Limit value type :	PNEC (Sewage treatment plant) ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Water (Including sewage plant)
Limit value :	100 mg/l
Limit value type :	PNEC (Industrial) ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )
Exposure route :	Water (Including sewage plant)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Industrial) ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )
Exposure route :	Soil
Limit value :	0,166 mg/kg
Limit value type :	PNEC (Aquatic, freshwater) ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Water (Including sewage plant)
Limit value :	0,327 mg/l
Limit value type :	PNEC (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Water (Including sewage plant)
Exposure time :	Long-term (continuous)
Limit value :	0,304 mg/l
Limit value type :	PNEC (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Water (Including sewage plant)
Exposure time :	Short-term (single)
Limit value :	0,5 mg/l
Limit value type :	PNEC (Industrial) ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Soil
Exposure time :	Long-term (continuous)



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

Limit value : 0,68 mg/kg  
Limit value type : PNEC (Sediment, freshwater) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Water (Including sewage plant)  
Limit value : 12,46 mg/kg  
Limit value type : PNEC soil ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Soil  
Limit value : 2,31 mg/kg  
Limit value type : PNEC (Sewage treatment plant) ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Water (Including sewage plant)  
Limit value : 6,58 mg/l  
Limit value type : PNEC (Aquatic, freshwater) ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Limit value : 0,0022 mg/l  
Limit value type : PNEC Intermittierende Einleitung ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Limit value : 0,009 mg/l  
Limit value type : PNEC (Aquatic, marine water) ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Limit value : 0,00022 mg/l  
Limit value type : PNEC (Soil) ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Limit value : 0,21 mg/kg  
Limit value type : PNEC (Sewage treatment plant) ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Limit value : 1 mg/l  
Limit value type : PNEC (Aquatic, freshwater) ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Limit value : 0,0022 mg/l  
Limit value type : PNEC Intermittierende Einleitung ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Limit value : 0,009 mg/l  
Limit value type : PNEC (Aquatic, marine water) ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Limit value : 0,00022 mg/l  
Limit value type : PNEC (Soil) ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Limit value : 0,21 mg/kg  
Limit value type : PNEC (Sewage treatment plant) ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Limit value : 1 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection

##### Suitable eye protection

goggles (EN 166)

##### Remark

Note DGUV-Rule 112-192.

#### Skin protection

##### Hand protection

Use safety gloves according to EN 374. Suitable glove materials: fluoro-rubber, butyl-rubber or nitrile-rubber. Please pay attention to the glove penetration times of the substances named below in chapter 2, according to the glove manufactures.

**Remark :** After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.

##### Body protection

**Required properties :** Antistatic, non-melting.

**Recommended material :** Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

**Remark** : Note DGUV-Rule 112-189. Note TRGS 401.

## Respiratory protection

Respiratory protection necessary at: Insufficient ventilation, insufficient exhaust or spray application.

### Suitable respiratory protection apparatus

Combination filter mask A2-P2 for short-term work.  
European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

### Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

## Occupational exposure controls

### Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid

**Colour** : According to product identification.

#### Odour

Like solvent.

#### Safety relevant basis data

<b>Melting point/melting range :</b>				not applicable
<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	approx.	120 - 200	°C
<b>Decomposition temperature :</b>				No data available
<b>Flash point :</b>		>	23 - 60	°C
<b>Ignition temperature :</b>				No data available
<b>Lower explosion limit :</b>		approx.	1	Vol-%
<b>Upper explosion limit :</b>		approx.	8	Vol-%
<b>Vapour pressure :</b>	( 50 °C )	<	100	hPa
<b>Density :</b>	( 20 °C )		1,2 - 1,7	g/cm <sup>3</sup>
<b>Solvent separation test :</b>	( 20 °C )	<	3	%
<b>Water solubility :</b>	( 20 °C )			Not or little soluble
<b>pH :</b>				No data available
<b>log P O/W :</b>				No data available
<b>Flow time :</b>	( 20 °C )	>	90	s
<b>Viscosity :</b>	( 23 °C )			No data available
<b>Cinematic viscosity :</b>	( 40 °C )	>	20,5	mm <sup>2</sup> /s
<b>Solid content :</b>			70 - 80	Wt %
<b>Odour threshold :</b>				not relevant
<b>Relative vapour density :</b>	( 20 °C )			No data available
<b>Vapourisation rate :</b>				No data available
<b>Maximum VOC content (EC) :</b>			30	Wt %
<b>Oxidising liquids :</b>	Not oxidising.			

### 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

No information available.

## 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

## 10.3 Possibility of hazardous reactions

No information available.

## 10.4 Conditions to avoid

No information available.

## 10.5 Incompatible materials

Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated. Oxidizing agent.

## 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Oral
Species :	Rat
Effective dose :	10760 mg/kg
Parameter :	LD50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	8500 mg/kg
Parameter :	LD50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )
Exposure route :	Oral
Species :	Rat
Effective dose :	5657 mg/kg
Parameter :	LD50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Oral
Species :	Rat
Effective dose :	2400 mg/kg
Parameter :	LD50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	8700 mg/kg
Parameter :	LD50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Oral
Species :	Mouse
Effective dose :	3200 mg/kg
Parameter :	LD50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg

##### Acute dermal toxicity

Parameter : ATEmix calculated

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

Exposure route : Dermal  
Effective dose : 27500 mg/kg  
Parameter : LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 14000 mg/kg  
Parameter : LD50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 5000 mg/kg  
Parameter : LD50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Exposure route : Dermal  
Species : Guinea pig  
Effective dose : > 8 g/kg  
Parameter : LD50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : 1580 mg/kg  
Parameter : LD50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg

## Acute inhalation toxicity

Parameter : ATEmix calculated  
Exposure route : Inhalation (vapour)  
Effective dose : 166,7 mg/l  
Parameter : LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 23,4 mg/kg  
Exposure time : 4 h  
Parameter : LC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 35,7 mg/l  
Parameter : LC50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 3813 ppm  
Exposure time : 6 h  
Parameter : LC50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 3,91 mg/l  
Exposure time : 8 h  
Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Species : Rat

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

Effective dose : 6350 mg/l

### Assessment/classification

Vapours may cause drowsiness and dizziness.

### Irritant and corrosive effects

#### Irritation to respiratory tract

May cause respiratory irritation.

## 11.3 Symptoms related to the physical, chemical and toxicological characteristics

#### In case of skin contact

Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Species :	Pimephales promelas (fathead minnow)
Effective dose :	18 mg/l
Exposure time :	96 h
Parameter :	LC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Species :	Oryzias latipes (Ricefish)
Effective dose :	> 100 mg/l
Exposure time :	96 h
Parameter :	LC50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )
Effective dose :	159 mg/l
Exposure time :	96 h
Parameter :	Acute (short-term) fish toxicity ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	28,3 mg/l
Exposure time :	96 h
Parameter :	LC50 ( XYLENE ; CAS No. : 1330-20-7 )
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	2,6 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )
Species :	Lepomis macrochirus (Bluegill)
Effective dose :	0,97 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	7,9 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )
Species :	Lepomis macrochirus (Bluegill)
Effective dose :	0,97 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	7,9 mg/l
Exposure time :	96 h
Method :	OECD 203

**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

#### Chronic (long-term) fish toxicity

Parameter : NOEC ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Species : Oryzias latipes (Ricefish)  
Effective dose : 47,5 mg/l  
Exposure time : 14 Days  
Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Effective dose : > 1,3 mg/l  
Exposure time : 56 Days

#### Acute (short-term) daphnia toxicity

Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 44 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 500 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 100 mg/l  
Exposure time : 48 h  
Method : OECD 202  
Parameter : Acute (short-term) daphnia toxicity ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 37 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 1 mg/l  
Exposure time : 24 h  
Method : OECD 202  
Parameter : EC50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 20 mg/l  
Exposure time : 24 h  
Method : OECD 202  
Parameter : EC50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 20 mg/l  
Exposure time : 24 h  
Method : OECD 202

#### Chronic (long-term) daphnia toxicity

Parameter : NOEC ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 100 mg/l  
Exposure time : 21 Days  
Parameter : NOEC ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 91 mg/l  
Method : OECD 211  
Parameter : Chronic (long-term) daphnia toxicity ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Species : Daphnia  
Effective dose : 30,4 mg/l  
Exposure time : 7 Days

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia  
Effective dose : 1,17 mg/l  
Exposure time : 7 Days  
Parameter : NOEC ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 1 mg/l  
Exposure time : 21 Days  
Parameter : NOEC ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 1 mg/l  
Exposure time : 21 Days  
Method : OECD 211

### Acute (short-term) algae toxicity

Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Desmodesmus subspicatus  
Effective dose : 647,7 mg/l  
Exposure time : 72 h  
Parameter : EL50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Desmodesmus subspicatus  
Effective dose : 200 mg/l  
Parameter : ErC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : > 1000 mg/l  
Exposure time : 3 h  
Parameter : EC50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Effective dose : > 100 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( 5-METHYLHEXAN-2-ONE ; CAS No. : 110-12-3 )  
Species : Algae  
Effective dose : > 100 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : 2,2 mg/l  
Exposure time : 72 h  
Method : OECD 201  
Parameter : EC50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Species : Desmodesmus subspicatus  
Effective dose : 1,68 mg/l  
Exposure time : 72 h  
Method : OECD 201  
Parameter : EC50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Species : Daphnia  
Effective dose : 20 mg/l  
Exposure time : 24 h  
Parameter : EC50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Species : Desmodesmus subspicatus  
Effective dose : 1,68 mg/l  
Exposure time : 72 h  
Method : OECD 201  
Parameter : EC50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Species : Daphnia  
Effective dose : 20 mg/l  
Exposure time : 24 h

### Chronic (long-term) algae toxicity

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : 0,44 mg/l  
Exposure time : 72 h

### Bacteria toxicity

Parameter : EC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Species : Mysisopsis bahia  
Effective dose : > 1000 mg/l  
Exposure time : 0,5 h

### Effects in sewage plants

Parameter : EC50 ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )  
Inoculum : Municipal  
Effective dose : > 100 mg/l  
Exposure time : 3 h  
Evaluation : Technically correct releases of minimal concentrations to adapted biological sewage plants, will not disturb the biodegradability of activated sludge.

Method : OECD 209

Parameter : EC50 ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )  
Inoculum : Municipal  
Effective dose : > 100 mg/l  
Exposure time : 3 h  
Evaluation : Technically correct releases of minimal concentrations to adapted biological sewage plants, will not disturb the biodegradability of activated sludge.

Method : OECD 209

## 12.2 Persistence and degradability

### Biodegradation

Parameter : Biodegradation ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Inoculum : Biodegradation  
Effective dose : 100 %  
Exposure time : 8 Days

Parameter : Biodegradation ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Inoculum : Biodegradation  
Effective dose : > 90 %  
Exposure time : 28 Days

Parameter : DOC reduction ( Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; CAS No. : 41556-26-7 )

Inoculum : Degree of elimination

Evaluation parameter : Aerobic

Effective dose : 38 %

Exposure time : 28 Days

Evaluation : Not readily biodegradable (according to OECD criteria) Moderately/partially biodegradable.

Method : OECD 301F

Parameter : DOC reduction ( Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacate ; CAS No. : 82919-37-7 )

Inoculum : Degree of elimination

Evaluation parameter : Aerobic

Effective dose : 38 %

Exposure time : 28 Days

Evaluation : Not readily biodegradable (according to OECD criteria) Moderately/partially biodegradable.

Method : OECD 301F

The solvent is biodegradable. In accordance with the required stability the product is poorly biodegradable.

### 12.3 Bioaccumulative potential

No information available.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

### Additional information

Do not allow uncontrolled discharge of product into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose according to legislation.

#### Product/Packaging disposal

##### Waste codes/waste designations according to EWC/AVV

###### Waste code product

EWC-Code: 08 01 11.

###### Waste code packaging

Uncleaned packaging: EWC-Code: 15 01 10. Cleaned packaging: EWC-Code: 15 01 04.

##### Waste treatment options

###### Appropriate disposal / Package

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### 13.2 Additional information

Note sections 7 and 8.

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

PAINT

#### Sea transport (IMDG)

PAINT

#### Air transport (ICAO-TI / IATA-DGR)

PAINT

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

Class(es) : 3

Classification code : F1

Hazard identification number (Kemler No.) : 30

Tunnel restriction code : D/E

Special provisions : LQ 5 I · E 1 · Transport in containers with max. 450 litres contents are not subject to the regulations of ADR/RID.

Hazard label(s) : 3

#### Sea transport (IMDG)

Class(es) : 3

EmS-No. : F-E / S-E

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
Revision date : 23.03.2020  
Print date : 23.03.2020

Version (Revision) : 10.0.0 (9.0.1)

Special provisions : LQ 5 I · E 1 · IMDG 2.3.2.5 (<= 450 l)  
Hazard label(s) : 3  
Air transport (ICAO-TI / IATA-DGR)  
Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

## 14.4 Packing group

III

## 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

## 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Other regulations (EU)

##### Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

##### National regulations

##### Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to AwSV

##### Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

15. Restrictions on use

### 16.2 Abbreviations and acronyms

TRGS: German Technical Rule for Hazardous Substances. BGR(I): Rule (Information) from the german employers liability insurance association. DGUV: German Statutory Accident Insurance. AwSV: Ordinance on plants for the handling of substances hazardous to water. VCI: German chemical industry association. EWC: European Waste Catalogue.

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2K-PUR-High-Solid-Lack 5732 (SORTE 5732)  
**Revision date :** 23.03.2020  
**Print date :** 23.03.2020

**Version (Revision) :** 10.0.0 (9.0.1)

---

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

## 16.6 Training advice

None

## 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---