

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

2K-PUR-AC-Lack 5743 (SORTE 5743)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Solvent-based coating. Intended purpose see technical data sheet.

Relevant identified uses

Products Category [PC]

Coatings and paints, thinners, paint removers

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co. KG, Industrielack
www.brillux-industrielack.de

Street : Otto-Hahn-Straße 14

Postal code/City : D-59423 Unna (Germany)

Telephone : +49 2303 8805-0

Telefax : +49 2303 8805-119

Information contact : E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english
Telephone: +49 551 19 24 0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

HYDROCARBONS, C9, AROMATICS

REACTION MASS OF ETHYLBENZENE AND XYLENE

REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5
REACTION PRODUCTS OF FATTY ACIDS, TALL-OIL, COMPOUNDS WITH OLEYLAMINE AND FATTY ACIDS, C18-UNSATURATED, TRIMERS, COMPOUNDS WITH OLEYLAMINE

Hazard statements

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P312 Call a POISON CENTER or a doctor if you feel unwell.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P391 Collect spillage.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Special rules for supplemental label elements for certain mixtures

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

TITANIUM DIOXIDE ; EC No. : 236-675-5; CAS No. : 13463-67-7

Weight fraction : $\geq 1 - < 30 \%$

Classification 1272/2008 [CLP] : Carc. 2 ; H351i

HYDROCARBONS, C9, AROMATICS ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5

Weight fraction : $\geq 20 - < 25 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

REACTION MASS OF ETHYLBENZENE AND XYLENE ; REACH No. : 01-2119486136-34 ; EC No. : 905-588-0

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; REACH No. : 01-2119491304-40 ; EC No. : 915-687-0; CAS No. : 1065336-91-5

Weight fraction : $\geq 0,25 - < 0,5 \%$

Classification 1272/2008 [CLP] : Repr. 2 ; H361f Skin Sens. 1A ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410 (M=1)

REACTION PRODUCTS OF FATTY ACIDS, TALL-OIL, COMPOUNDS WITH OLEYLAMINE AND FATTY ACIDS, C18-UNSATURATED, TRIMERS, COMPOUNDS WITH OLEYLAMINE ; REACH No. : 01-2120101675-63 ; EC No. : 916-741-6

Weight fraction : $\geq 0,1 - < 0,5 \%$

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Classification 1272/2008 [CLP] : STOT RE 2 ; H373 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1A ; H317

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change contaminated, saturated clothing. When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye.

Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO₂), water spray.

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide (CO), carbon dioxide (CO₂) and pyrolysis products, toxic.

5.3 Advice for firefighters

Special protective equipment for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Avoid: Inhalation of vapours or spray/mists Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Never use pressure to empty container. Only allow access to authorised staff.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Advices on general occupational hygiene

Wear personal protection equipment (refer to section 8). When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Floors should be impervious, resistant to liquids and easy to clean. Provide adequate ventilation as well as local exhaust at critical locations. Keep container tightly closed.

Hints on joint storage

Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place.

Protect against : Heat. Humidity.

7.3 Specific end use(s)

Solvent-based coating. Intended purpose see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : STEL (EC)

Limit value : 200 ppm / 884 mg/m³

Remark : Ethylbenzol H

Version :

Limit value type (country of origin) : TWA (EC)

Limit value : 100 ppm / 442 mg/m³

Remark : Ethylbenzol H

Version :

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : STEL (EC)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Limit value : 150 ppm / 723 mg/m³
Version : 20.06.2019
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 241 mg/m³
Version : 20.06.2019

DNEL-/PNEC-values

DNEL/DMEL

HYDROCARBONS, C9, AROMATICS

Limit value type : DNEL/DMEL (Consumer)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 11 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 32 mg/m³
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 11 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Professional)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 25 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Professional)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 150 mg/m³

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 65,3 mg/m³
Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 260 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : = 1,6 mg/kg
Assessment factor : 1 D
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 14,8 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 260 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Exposure frequency : Short-term
Limit value : = 289 mg/m³
Limit value type : DNEL worker (local and systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 221 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 211 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 442 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : = 180 mg/kg
Assessment factor : 1 D

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 102,34 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 96 mg/kg
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 48 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 7 mg/kg
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 480 mg/m³

PNEC

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,327 mg/l
Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : = 0,327 mg/l
Limit value type : PNEC (Sediment, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 12,64 mg/kg
Limit value type : PNEC (Sediment, marine water)
Exposure route : Water (Including sewage plant)
Limit value : = 12,64 mg/kg
Limit value type : PNEC soil
Exposure route : Soil

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Limit value : 2,31 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 6,58 mg/l
N-BUTYL ACETATE ; CAS No. : 123-86-4
Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,18 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Exposure route : Water (Including sewage plant)
Limit value : 0,36 mg/l
Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 0,018 mg/l
Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 0,981 mg/kg
Limit value type : PNEC (Sediment, marine water)
Exposure route : Soil
Limit value : 0,0981 mg/kg
Limit value type : PNEC soil
Exposure route : Soil
Limit value : 0,0903 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 35,6 mg/l

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

goggles (EN 166)

Skin protection

Hand protection

Use safety gloves according to EN 374. Suitable glove materials: fluoro-rubber, butyl-rubber or nitrile-rubber. Please pay attention to the glove penetration times of the substances named below in section 2, according to the glove manufactures.

Remark : After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Required properties : Antistatic, non-melting.

Recommended material : Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Respiratory protection

Respiratory protection necessary at: Insufficient ventilation, insufficient exhaust or spray application.

Suitable respiratory protection apparatus

Combination filter mask A2-P2 for short-term work.

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

Other protection measures

Technical measures and the application of suitable work processes have priority over personal protection equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Physical state : Liquid
Colour : According to product identification.

Odour

Like solvent.

Safety characteristics

Melting point/freezing point :			not applicable	
Initial boiling point and boiling range :	(1013 hPa)	ca	120 - 200	°C
Decomposition temperature :			No data available	
Flash point :		>	23 - 60	°C
Auto-ignition temperature :			No data available	
Lower explosion limit :		ca	1	Vol-%
Upper explosion limit :		ca	10	Vol-%
Vapour pressure :	(50 °C)	<	100	hPa
Density :	(20 °C)		1 - 1,5	g/cm ³
Solvent separation test :	(20 °C)	<	3	%
Water solubility :	(20 °C)		practically insoluble	
pH :			No data available	
Flow time :	(20 °C)	>	90	s
Kinematic viscosity :	(23 °C)	>	20,5	mm ² /s
Solid content :			No data available	

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated. Oxidizing agent.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 (HYDROCARBONS, C9, AROMATICS)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 6800 mg/kg
Parameter :	LD50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Exposure route :	Oral

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Species : Rat
Effective dose : 3523 - 4000 mg/kg
Parameter : LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Oral
Species : Rat
Effective dose : 10760 mg/kg
Parameter : LC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)
Exposure route : Oral
Species : Rat
Effective dose : > 2000 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : 14524 mg/kg
Parameter : LD50 (HYDROCARBONS, C9, AROMATICS)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 3400 mg/kg
Parameter : LD50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Exposure route : Dermal
Species : Rabbit
Effective dose : 12126 mg/kg
Parameter : LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 14000 mg/kg
Parameter : LC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)
Exposure route : Dermal
Species : Rat
Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalation (vapour)
Effective dose : 145,2 mg/l
Parameter : LC50 (HYDROCARBONS, C9, AROMATICS)
Exposure route : Inhalation
Species : Rat
Effective dose : > 10,2 mg/l
Exposure time : 4 h
Parameter : LC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Exposure route : Inhalation (vapour)
Species : Rat
Effective dose : 10 - 20 mg/l
Exposure time : 4 h
Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Species : Rat
Effective dose : 23,4 mg/kg
Exposure time : 4 h

Corrosion

Irritation to respiratory tract

May cause respiratory irritation.

Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

STOT-single exposure

STOT SE 3

Narcotic effects

Vapours may cause drowsiness and dizziness.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of skin contact

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (HYDROCARBONS, C9, AROMATICS)

Species : Oncorhynchus mykiss (Rainbow trout)

Effective dose : 9,2 mg/l

Exposure time : 96 h

Parameter : LC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)

Species : Acute (short-term) fish toxicity

Evaluation parameter : Oncorhynchus mykiss

Effective dose : = 2,6 mg/l

Exposure time : 96 h

Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Pimephales promelas (fathead minnow)

Effective dose : 18 mg/l

Exposure time : 96 h

Parameter : LC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Species : Lepomis macrochirus (Bluegill)

Effective dose : 0,97 mg/l

Exposure time : 96 h

Parameter : LC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Species : Oncorhynchus mykiss (Rainbow trout)

Effective dose : 7,9 mg/l

Exposure time : 96 h

Acute (short-term) toxicity to crustacea

Parameter : EC50 (HYDROCARBONS, C9, AROMATICS)

Species : Daphnia magna (Big water flea)

Effective dose : 3,2 mg/l

Exposure time : 48 h

Parameter : LC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)

Species : Acute (short-term) toxicity to crustacea

Evaluation parameter : Daphnia magna

Effective dose : = 1 mg/l

Exposure time : 24 h

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Daphnia magna (Big water flea)

Effective dose : 44 mg/l

Exposure time : 48 h

Parameter : EC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Species : Daphnia magna (Big water flea)
Effective dose : 20 mg/l
Exposure time : 24 h

Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Species : Daphnia magna (Big water flea)
Effective dose : 1 mg/l
Exposure time : 21 D

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : ErC50 (HYDROCARBONS, C9, AROMATICS)

Species : Pseudokirchneriella subcapitata
Effective dose : 2,6 - 2,9 mg/l
Exposure time : 72 h

Parameter : EC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)

Species : Scenedesmus capricornutum
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : = 2,2 mg/l
Exposure time : 73 h

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Desmodesmus subspicatus
Effective dose : 647,7 mg/l
Exposure time : 72 h

Parameter : EL50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Desmodesmus subspicatus
Effective dose : 200 mg/l

Parameter : EC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Species : Desmodesmus subspicatus
Effective dose : 1,68 mg/l
Exposure time : 72 h

Parameter : EC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Species : Daphnia
Effective dose : 20 mg/l
Exposure time : 24 h

Sewage treatment plant

Parameter : Effects in sewage plants (REACTION MASS OF ETHYLBENZENE AND XYLENE)

Inoculum : Activated sludge
Effective dose : = 16 mg/l
Exposure time : 28 D

Parameter : EC50 (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)

Inoculum : Municipal
Effective dose : > 100 mg/l
Exposure time : 3 h

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (REACTION MASS OF ETHYLBENZENE AND XYLENE)

Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : = 90 %

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

Test duration : 28 D
Parameter : DOC reduction (REACTION MASS OF BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE ; CAS No. : 1065336-91-5)
Inoculum : Degree of elimination
Evaluation parameter : Aerobic
Degradation rate : 38 %
Test duration : 28 D

The solvent is biodegradable. In accordance with the required stability the product is poorly biodegradable.

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Bioconcentration factor (BCF)
Value : = 25,9

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose of waste according to applicable legislation.

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

08 01 11* (Waste paint and varnish containing organic solvents or other dangerous substances)

After intended use

Waste codes/waste designations according to EWC/AVV

Uncleaned packaging: 15 01 10* (Packaging containing residues of or contaminated by dangerous substances)

Cleaned packaging: 15 01 04 (Metallic packaging)

Other disposal recommendations

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

Note sections 7 and 8.

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT

Sea transport (IMDG)

PAINT (HYDROCARBONS, C9, AROMATICS)

Air transport (ICAO-TI / IATA-DGR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

PAINT

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : LQ 5 I · E 1 · ADR : - (<= 5 l ; 2.2.3.1.5 + N)
Hazard label(s) : 3 / N

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / ~~S-E~~
Special provisions : LQ 5 I · E 1 · IMDG 2.3.2.5 + P (<= 5 l)
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes
Sea transport (IMDG) : Yes (P)
Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40, 75

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

AwSV: Ordinance on plants for the handling of substances hazardous to water. BGR(I): Rule (Information) from the german employers liability insurance association. DGUV: German Statutory Accident Insurance. EWC: European Waste Catalogue. TRGS: German Technical Rule for Hazardous Substances. VCI: German chemical industry association.

16.3 Key literature references and sources for data

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2K-PUR-AC-Lack 5743 (SORTE 5743)
Revision date : 19.07.2022
Print date : 19.07.2022

Version (Revision) : 19.0.0 (18.0.0)

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351i	Suspected of causing cancer if inhaled.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.