

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
Revision date : 24.10.2024  
Print date : 24.10.2024

Version (Revision) : 16.0.0 (15.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
Unique Formula Identifier : DQY0-H0SM-H000-VCFC

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Hardener for 2C-EP-paints

#### Relevant identified uses

##### Products Category [PC]

Coatings and paints, thinners, paint removers

#### Remark

The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Brillux GmbH & Co. KG, Industrielack  
www.brillux-industrielack.de

**Street :** Otto-Hahn-Straße 14

**Postal code/City :** D-59423 Unna (Germany)

**Telephone :** +49 2303 8805-0

**Telefax :** +49 2303 8805-119

**Information contact :** E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

### 1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english  
Telephone: +49 551 19 24 0

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)

##### Signal word

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

Warning

### Hazard components for labelling

HYDROCARBONS, C9, AROMATICS  
REACTION MASS OF ETHYLBENZENE AND XYLENE  
AMINES, POLYETHYLENEPOLY-, TRIETHYLENETETRAMINE FRACTION ; CAS No. : 90640-67-8  
REACTION PRODUCTS OF FATTY ACIDS, TALL-OIL, COMPOUNDS WITH OLEYLAMINE AND FATTY ACIDS, C18-UNSATURATED, TRIMERS, COMPOUNDS WITH OLEYLAMINE

### Hazard statements

H226 Flammable liquid and vapour.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### 2.3 Other hazards

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

FATTY ACIDS, TALL-OIL, DIMERS, POLYMERS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE ; EC No. : 630-460-3; CAS No. : 68915-18-4

Weight fraction :  $\geq 40 - < 45 \%$   
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

HYDROCARBONS, C9, AROMATICS ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5

Weight fraction :  $\geq 35 - < 40 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

REACTION MASS OF ETHYLBENZENE AND XYLENE ; REACH No. : 01-2119486136-34 ; EC No. : 905-588-0

Weight fraction :  $\geq 15 - < 20 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

AMINES, POLYETHYLENEPOLY-, TRIETHYLENETETRAMINE FRACTION ; REACH No. : 01-2119487919-13 ; EC No. : 292-588-2; CAS No. : 90640-67-8

Weight fraction :  $\geq 0,5 - < 1 \%$   
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Skin Sens. 1 ; H317 Aquatic Chronic 3 ; H412

REACTION PRODUCTS OF FATTY ACIDS, TALL-OIL, COMPOUNDS WITH OLEYLAMINE AND FATTY ACIDS, C18-UNSATURATED, TRIMERS, COMPOUNDS WITH OLEYLAMINE ; REACH No. : 01-2120101675-63 ; EC No. : 916-741-6

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

Weight fraction :  $\geq 0,1 - < 0,5 \%$   
Classification 1272/2008 [CLP] : STOT RE 2 ; H373 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1A ; H317

### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Change contaminated, saturated clothing. When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

#### After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye.

#### Following ingestion

Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest.

#### Self-protection of the first aider

No direct artificial respiration to be given by first aider.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), water spray.

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and pyrolysis products, toxic.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Use suitable breathing apparatus.

### 5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
Revision date : 24.10.2024  
Print date : 24.10.2024

Version (Revision) : 16.0.0 (15.0.0)

Provide adequate ventilation. See protective measures under point 7 and 8.

## 6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

## 6.3 Methods and material for containment and cleaning up

### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

## 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Avoid: Inhalation of vapours or spray/mists Never use pressure to empty container. Only allow access to authorised staff. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Floors should be impervious, resistant to liquids and easy to clean. Provide adequate ventilation as well as local exhaustion at critical locations. Keep container tightly closed.

#### Hints on joint storage

Storage class (TRGS 510) : 3

#### Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

#### Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place.

Protect against : Heat. Humidity.

### 7.3 Specific end use(s)

Hardener for 2C-EP-paints

#### Industrial sector specific solutions

Note DGUV-Rule 100-500, section 2.29 (processing coating materials).

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

HYDROCARBONS, C9, AROMATICS

Limit value type (country of origin) : TRGS 900 ( D )

Parameter : Group limit for the calculation of the occupational exposure limit for hydrocarbon mixtures (see section 2.9 of Technical Rule 900).

Limit value : 50 mg/m<sup>3</sup>

Version :

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : TRGS 900 ( D )

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

Limit value : 100 ppm / 440 mg/m<sup>3</sup>  
Peak limitation : 4  
Remark : Xylol  
Version : 01.10.1993  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : Ethylbenzol H, Y, DFG  
Version : 01.10.1993  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : Ethylbenzol H  
Version :  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Ethylbenzol H  
Version :

### Biological limit values

#### REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift  
Limit value : 0,15 mg/dl  
Remark : Xylol  
Version : 01.10.1993  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift  
Limit value : 2 g/l  
Remark : Xylol  
Version : 01.10.1993  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift  
Limit value : 250 mg/g Creatinine  
Remark : Ethylbenzol  
Version : 01.10.1993

### DNEL-/PNEC-values

#### DNEL/DMEL

##### HYDROCARBONS, C9, AROMATICS

Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 11 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 32 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 11 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Professional)  
Exposure route : Dermal  
Exposure frequency : Long-term

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

Limit value : 25 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Professional)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 150 mg/m<sup>3</sup>

**REACTION MASS OF ETHYLBENZENE AND XYLENE**

Limit value type : DNEL Consumer (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 65,3 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 260 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : = 1,6 mg/kg  
Assessment factor : 1 D

Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 14,8 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 260 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 289 mg/m<sup>3</sup>

Limit value type : DNEL worker (local and systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 221 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 211 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 442 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : = 180 mg/kg  
Assessment factor : 1 D

### PNEC

**REACTION MASS OF ETHYLBENZENE AND XYLENE**

Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,327 mg/l

Limit value type : PNEC (Aquatic, marine water)  
Exposure route : Water (Including sewage plant)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

Limit value : = 0,327 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 12,64 mg/kg  
Limit value type : PNEC (Sediment, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : = 12,64 mg/kg  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 2,31 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 6,58 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection

##### Suitable eye protection

goggles

##### Recommended eye protection articles

EN 166

##### Remark

Note DGUV-Rule 112-192.

#### Skin protection

##### Hand protection

Use safety gloves according to EN 374. Suitable glove materials: fluoro-rubber, butyl-rubber or nitrile-rubber. Please pay attention to the glove penetration times of the substances named below in section 2, according to the glove manufactures.

**Remark :** After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.

##### Body protection

**Required properties :** Antistatic, non-melting.

**Recommended material :** Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

**Remark :** Note DGUV-Rule 112-189. Note TRGS 401.

#### Respiratory protection

Respiratory protection necessary at: Insufficient ventilation, insufficient exhaust or spray application.

##### Suitable respiratory protection apparatus

Combination filter mask A2-P2 for short-term work.

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

##### Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

#### Other protection measures

Technical measures and the application of suitable work processes have priority over personal protection equipment.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state :** Pasty to liquid

**Colour :** According to product identification.

#### Odour

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
Revision date : 24.10.2024  
Print date : 24.10.2024

Version (Revision) : 16.0.0 (15.0.0)

Like solvent.

## Safety characteristics

Melting point/freezing point :				not applicable
Initial boiling point and boiling range :	( 1013 hPa )	>	120	°C
Decomposition temperature :				No data available
Flash point :		>	23 - 60	°C
Auto-ignition temperature :		>	300	°C
Lower explosion limit :		approx.	0,7	Vol-%
Upper explosion limit :		approx.	10	Vol-%
Vapour pressure :	( 50 °C )	<	50	hPa
Density :	( 20 °C )		0,9 - 1	g/cm <sup>3</sup>
Solvent separation test :	( 20 °C )	<	3	%
Water solubility :	( 20 °C )			practically insoluble
pH :		approx.	9 - 10	
log P O/W :				No data available
Flow time :	( 20 °C )	>	60	s ISO cup 6 mm
Cinematic viscosity :	( 40 °C )	>	20,5	mm <sup>2</sup> /s
Odour threshold :				not relevant
Relative vapour density :	( 20 °C )			No data available
Vapourisation rate :				No data available
Oxidising liquids :	Not oxidising.			

## 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

No information available.

### 10.4 Conditions to avoid

No information available.

### 10.5 Incompatible materials

Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated. Oxidizing agent.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Acute oral toxicity

Parameter :	ATEmix
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 ( HYDROCARBONS, C9, AROMATICS )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 6800 mg/kg
Parameter :	LD50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

Exposure route : Oral  
Species : Rat  
Effective dose : 3523 - 4000 mg/kg

### Acute dermal toxicity

Parameter : ATEmix  
Exposure route : Dermal  
Effective dose : 6320 mg/kg  
Parameter : LD50 ( HYDROCARBONS, C9, AROMATICS )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 3400 mg/kg  
Parameter : LD50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 12126 mg/kg

### Acute inhalation toxicity

Parameter : ATEmix  
Exposure route : Inhalation (vapour)  
Effective dose : 63,2 mg/l  
Parameter : LC50 ( HYDROCARBONS, C9, AROMATICS )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 10,2 mg/l  
Exposure time : 4 h  
Parameter : LC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Exposure route : Inhalation (vapour)  
Species : Rat  
Effective dose : 10 - 20 mg/l  
Exposure time : 4 h

### Corrosion

#### Irritation to respiratory tract

May cause respiratory irritation.

### STOT-single exposure

#### STOT SE 3

#### Narcotic effects

Vapours may cause drowsiness and dizziness.

## 11.3 Symptoms related to the physical, chemical and toxicological characteristics

#### In case of skin contact

Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( HYDROCARBONS, C9, AROMATICS )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Effective dose : 9,2 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Species : Acute (short-term) fish toxicity  
Evaluation parameter : Oncorhynchus mykiss  
Effective dose : = 2,6 mg/l  
Exposure time : 96 h

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( HYDROCARBONS, C9, AROMATICS )  
Species : Daphnia magna (Big water flea)  
Effective dose : 3,2 mg/l  
Exposure time : 48 h  
Parameter : LC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Species : Acute (short-term) toxicity to crustacea  
Evaluation parameter : Daphnia magna  
Effective dose : = 1 mg/l  
Exposure time : 24 h

### Acute (short-term) toxicity to algae and cyanobacteria

Parameter : ErC50 ( HYDROCARBONS, C9, AROMATICS )  
Species : Pseudokirchneriella subcapitata  
Effective dose : 2,6 - 2,9 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Species : Scenedesmus capricornutum  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : = 2,2 mg/l  
Exposure time : 73 h

### Sewage treatment plant

Parameter : Effects in sewage plants ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Inoculum : Activated sludge  
Effective dose : = 16 mg/l  
Exposure time : 28 D

## 12.2 Persistence and degradability

### Biodegradation

Parameter : Biodegradation ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : = 90 %  
Test duration : 28 D

The solvent is biodegradable. In accordance with the required stability the product is poorly biodegradable.

## 12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Bioconcentration factor (BCF)  
Value : = 25,9

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

### Additional information

Do not allow uncontrolled discharge of product into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose of waste according to applicable legislation.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

**Directive 2008/98/EC (Waste Framework Directive)**

**Before intended use**

**Waste codes/waste designations according to EWC/AVV**

08 01 11\* (Waste paint and varnish containing organic solvents or other dangerous substances)

**After intended use**

**Waste codes/waste designations according to EWC/AVV**

Uncleaned packaging: 15 01 10\* (Packaging containing residues of or contaminated by dangerous substances)

Cleaned packaging: 15 01 04 (Metallic packaging)

**Other disposal recommendations**

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**13.2 Additional information**

Note sections 7 and 8.

**SECTION 14: Transport information**

**14.1 UN number**

UN 1263

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**

PAINT RELATED MATERIAL

**Sea transport (IMDG)**

PAINT RELATED MATERIAL ( HYDROCARBONS, C9, AROMATICS )

**Air transport (ICAO-TI / IATA-DGR)**

PAINT RELATED MATERIAL

**14.3 Transport hazard class(es)**

**Land transport (ADR/RID)**

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler No.) :** 30  
**Tunnel restriction code :** D/E  
**Special Provisions :** LQ 5 I · E 1 · ADR : - (<= 5 l ; 2.2.3.1.5 + N)  
**Hazard label(s) :** 3 / N

**Sea transport (IMDG)**

**Class(es) :** 3  
**EmS-No. :** F-E / S-E  
**Special Provisions :** LQ 5 I · E 1 · IMDG 2.3.2.5 + P (<= 5 l)  
**Hazard label(s) :** 3 / N

**Air transport (ICAO-TI / IATA-DGR)**

**Class(es) :** 3  
**Special Provisions :** E 1  
**Hazard label(s) :** 3

**14.4 Packing group**

III

**14.5 Environmental hazards**

**Land transport (ADR/RID) :** Yes

**Sea transport (IMDG) :** Yes (P)

**Air transport (ICAO-TI / IATA-DGR) :** Yes

**14.6 Special precautions for user**

None

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
Revision date : 24.10.2024  
Print date : 24.10.2024

Version (Revision) : 16.0.0 (15.0.0)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3

##### Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

##### National regulations

##### Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

##### Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

#### 15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 15. Restrictions on use · 15. Water hazard class

#### 16.2 Abbreviations and acronyms

AwSV: Ordinance on plants for the handling of substances hazardous to water. BGR(I): Rule (Information) from the German employers liability insurance association. DGUV: German Statutory Accident Insurance. EWC: European Waste Catalogue. TRGS: German Technical Rule for Hazardous Substances. VCI: German chemical industry association.

#### 16.3 Key literature references and sources for data

None

#### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

#### 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### 16.6 Training advice

None

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**



**Trade name :** EP-Härter 5797, Transparent bräunlich (5797.-.0200)  
**Revision date :** 24.10.2024  
**Print date :** 24.10.2024

**Version (Revision) :** 16.0.0 (15.0.0)

---

**16.7 Additional information**

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---