according to Regulation (EC) 1907/2006



Product name : Epoxypulver EP 5831 (SORTE 5831)

Revision: 03.11.2009 **Version:** 1.0.0

Print date : 03.11.2009

01. Identification of the substance/preparation and of the company/undertaking

Product name

Epoxypulver EP 5831 (SORTE 5831)

Use of the substance / preparation

Powder coating. Intended purpose see technical data sheet.

Manufacturer/Supplier

Brillux GmbH & Co. KG, Industrielack www.brillux-industrielack.de

Street/P.O.Box

Otto-Hahn-Straße 14

Country code/Postal code/Town/City

D-59423 Unna

Telephone / Telefax

+49 (0)2303 8805-0 / +49 (0)2303 8805-119

Emergency information

After the office hours:

(Advisory board for symptom of poisoning, Berlin)

Telephon: +49 (0)30 19240

Contact

info@brillux-industrielack.de

02. Hazards identification

Hazard designation

May cause sensitisation by skin contact.

Classification: R 43

Additional information

This product is dangerous concerning EC-guideline 1999/45/EC.

03. Composition/information on ingredients

Hazardous components

BIGUANID ; EC-No. : 202-268-6; CAS-No. : 93-69-6

Percentage: 1-5% Classification: R 43 Xi; R 36

For the wording of the listed risk phrases refer to section 16.

04. First-aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. Unconsciousness: lateral position - call a physician.

After inhalation

Take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor in case.

After skin contact

Wash away with soap and water and rinse. Do not use solvents or thinners.

After eye contact

Call a doctor in case. Flush plenty with water (opened eyelid)

After ingestion

Call a doctor and tell him the exactly substance. Keep at rest. Do not induce vomiting.

05. Fire-fighting measures

Page: 1 / 5

(EN/D)

according to Regulation (EC) 1907/2006



Product name : Epoxypulver EP 5831 (SORTE 5831)

Revision: 03.11.2009 **Version:** 1.0.0

Print date : 03.11.2009

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray. The fire fighting for manuell and self-acting powder coating systems conformable ZH 1/443, ZH 1/444 the extingshent agent CO2 can be used by movable tool and fight fire extingquishing system. For using other extingshent agent than CO2 the effectiveness must be proved.

Unsuitable extinguishing media

Waterjet. Inert gas with high pressure.

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool endangered containers with water in case of fire.

06. Accidental release measures

Personal precautions

Remove ignition sources. Refer to protective measures listed in sections 7 and 8. Avoid dust development. Do not inhale product dusts.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/collecting

Contain and collect spillage with a vacuum cleaner or by wet brushing and place in container for disposal according to local regulations. (See section 13). (Vacuum cleaner construction B1, appropriate to suck up combustible dust) Do not use a dry brush as dust clouds can be created.

07. Handling and storage

Information for safe handling

Prevent the creation of flammable or explosive concentrations of dust in air and avoid dust concentration higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Comply with the health and safety at work laws.

Information about protection against explosions and fires

Avoid dust development, danger of dust explosion. Take precautionary measures against static discharges. Operators should wear antistatic footwear and clothing. No sparking tools should be used.

Requirements to be met by storerooms and containers

Electrical equipment should be pr.tected to the appropriate standard. Floors should be of the conducting type. Make sure that ventilation is adequate. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store the foodstuffs separately.

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep containers dry and cool.

Storage class (VCI): 13

Specific uses

Powder coating. Intended purpose see technical data sheet.

08. Exposure controls/personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Page: 2/5

according to Regulation (EC) 1907/2006



Product name : Epoxypulver EP 5831 (SORTE 5831)

Revision: 03.11.2009 **Version:** 1.0.0

Print date: 03.11.2009

Personal protective equipment

Respiratory protection

Breathing filter (particle): P2

Hand protection

Use protective gloves. Use protective cream in case of a longer and continued contact of skin. After washing hands replace lost skin fat by fat containing skin creams.

Eye protection

Use safety glasses.

Body protection

Personel should wear protective clothings and all parts of the body should be washed after contact. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder is avoided.

09. Physical and chemical properties

Image

Form: Powder

Colour : According to product identification.

Odour : Poor, characteristic

Relevant safety data

Melting point / range : 50 °C Decomposition point / range: 250 °C Flash point: not applicable °C Ignition temperature: 450 Lower explosion limit: 50 - 70 ca. g/m³ Upper explosion limit : no data available

Vapour pressure :($50 \, ^{\circ}\text{C}$)not applicableDensity :($20 \, ^{\circ}\text{C}$)1,2 - 1,7 g/cm³

Solubility in water: (20 °C) insoluble

Solids content: 100 % b.w.

Additional information

The physical specifications are approximate values and refer to the used safety relevant component(s).

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

Materials to avoid

None known.

Hazardous decomposition products

None, if handled according to order. When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Experience on practice

There are no data available on the product itself. Powder coatings can cause localised skin irritation in folds of the skin or in contact with tight clothing.

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Page: 3 / 5

according to Regulation (EC) 1907/2006



Product name : Epoxypulver EP 5831 (SORTE 5831)

Revision: 03.11.2009 **Version:** 1.0.0

Print date : 03.11.2009

Details on elimination (persistance / degradibility)

There are no data available on the product itself.

Additional ecological information

Do not empty into waters or drains.

13. <u>Disposal considerations</u>

Product

Recommendation

Can be taken to a suitable incineration centre in oberservance of local regulations.

Waste key

EWC-Code: 08 02 01.

Contaminated packaging

Recommendation

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

14. Transport information

Land transport ADR/RID

Classification

Class:

Maritime transport IMDG/GGVSea

Classification

IMDG-Code:

Air transport ICAO-TI and IATA-DGR

Classification

Class:

Packaging

15. Regulatory information

Classification according to EC directives

Danger symbol and danger designation



Xi ; Irritant

Hazard-determining components of labelling

BIGUANID; CAS-No.: 93-69-6

R-phrases

43 May cause sensitisation by skin contact.

S-phrases

35 This material and its container must be disposed of in a safe way.

Wear suitable gloves.

In case of insufficient ventilation, wear suitable respiratory equipment.

Avoid contact with skin.Do not breathe dust.

National regulatory information

Emission control act ("TA-Luft")

Sum organic substances class I: 0,5 - 10 %

Water pollution classification

Class: 1 according VwVwS

Page: 4/5

(EN/D)

according to Regulation (EC) 1907/2006



Product name : Epoxypulver EP 5831 (SORTE 5831)

Revision: 03.11.2009 **Version:** 1.0.0

Print date : 03.11.2009

16. Other information

Restrictions on use recommended by the manufacturer

Look at the technical data sheet.

Further information

R-Phrases of components

36 Irritating to eyes.

43 May cause sensitisation by skin contact.

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Page: 5 / 5