

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Hydro-2K-PUR-Lack 5861 (SORTE 5861)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Waterborne coating. Intended purpose see technical data sheet.

Relevant identified uses

Product Categories [PC]

PC9 - Coatings and paints, fillers, putties, thinners

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co. KG, Industrielack
www.brillux-industrielack.de

Street : Otto-Hahn-Straße 14

Postal code/city : D-59423 Unna

Telephone : +49 2303 8805-0

Telefax : +49 2303 8805-119

Information contact : E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english
Telephone: +49 551 19 24 0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

Additional information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH208 Contains REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

2-BUTOXYETHANOL ; REACH registration No. : 01-2119475108-36 ; EC No. : 203-905-0; CAS No. : 111-76-2

Weight fraction : $\geq 1 - < 5\%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

Eye Irrit. 2 ; H319
3-BUTOXYPROPAN-2-OL ; EC No. : 225-878-4; CAS No. : 5131-66-8
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; REACH registration No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 64742-95-6
Weight fraction : $\geq 1 - < 2,5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change contaminated, saturated clothing. When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect uninjured eye.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO₂), water spray.

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide (CO), carbon dioxide (CO₂) and pyrolysis products, toxic.

5.3 Advice for firefighters

Special protective equipment for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Avoid: Inhalation of vapours or spray/mists Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Never use pressure to empty container. Only allow access to authorised staff.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advices on general occupational hygiene

Wear personal protection equipment (refer to section 8). When using do not eat, drink, smoke, sniff. Always close containers tightly after the removal of product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Floors should be impervious, resistant to liquids and easy to clean. Keep container tightly closed.

Hints on joint storage

Storage class (TRGS 510) : 12

Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place.

Protect against : Heat, frost and humidity.

7.3 Specific end use(s)

Waterborne coating. Intended purpose see technical data sheet.

Industrial sector specific solutions

Note DGUV-Rule 100-500, section 2.29 (processing coating materials). Note DGUV-Rule 109-013.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-BUTOXYETHANOL ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 10 ppm / 49 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

Peak limitation : 2(II)
Remark : H,Y
Version : 29.03.2019
Limit value type (country of origin) : STEL (EC)
Limit value : 50 ppm / 246 mg/m³
Remark : H
Version : 31.01.2018
Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 98 mg/m³
Remark : H
Version : 31.01.2018
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 100 mg/m³
Peak limitation : 2(II)
Remark : AGS
Version :
Limit value type (country of origin) : TWA (D)
Limit value : 25 mg/kg
Version :
2,2',2''-NITRILOTRIETHANOL ; CAS No. : 102-71-6
Limit value type (country of origin) : MAK - Grenzwerte in der Luft am Arbeitsplatz (D)
Parameter : measured as the inhaleable fraction
Limit value : 5 mg/m³
Version :
Limit value type (country of origin) : TRGS 900 (D)
Parameter : E: inhalable fraction
Limit value : 1 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 29.03.2019

Biological limit values

2-BUTOXYETHANOL ; CAS No. : 111-76-2
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts
Limit value : 100 mg/l
Version : 29.03.2019
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts
Limit value : 150 mg/g Kr
Version : 29.03.2019

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL/DMEL (Industrial) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : 89 mg/kg
Limit value type : DNEL/DMEL (Industrial) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 663 mg/m³
Limit value type : DNEL/DMEL (Industrial) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

Exposure frequency : Long-term (repeated)
Limit value : 75 mg/kg
Limit value type : DNEL/DMEL (Industrial) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 98 mg/m³
Limit value type : DNEL worker (local) (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 25 mg/kg
Limit value type : DNEL worker (local) (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 150 mg/m³

PNEC

Limit value type : PNEC (Industrial) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Water (Including sewage plant)
Limit value : 8,8 mg/l
Limit value type : PNEC (Industrial) (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Soil
Limit value : 2,8 mg/kg

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

goggles (EN 166)

Remark

Note DGUV-Rule 112-192.

Skin protection

Hand protection

Use safety gloves according to EN 374. Suitable glove materials: fluoro-rubber, butyl-rubber or nitrile-rubber. Please pay attention to the glove penetration times of the substances named below in chapter 2, according to the glove manufactures.

Remark : After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.

Body protection

Required properties : Antistatic, non-melting.

Recommended material : Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Remark : Note DGUV-Rule 112-189. Note TRGS 401.

Respiratory protection

Respiratory protection necessary at: Insufficient ventilation, insufficient exhaust or spray application.

Suitable respiratory protection apparatus

Combination filter mask A2-P2 for short-term work.

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

Occupational exposure controls

Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : According to product identification.

Odour

product specific, characteristic.

Safety relevant basis data

Melting point/melting range :			not applicable	
Initial boiling point and boiling range :	(1013 hPa)	>	100	°C
Decomposition temperature :			No data available	
Flash point :			not applicable	
Ignition temperature :			No data available	
Lower explosion limit :		approx.	0,7	Vol-%
Upper explosion limit :		approx.	7,5	Vol-%
Vapour pressure :	(50 °C)	<	150	hPa
Density :	(20 °C)		1 - 1,5	g/cm ³
Water solubility :	(20 °C)		consolute miscible	
pH :			7,5 - 8	
log P O/W :			No data available	
Flow time :	(20 °C)	>	60	s DIN-cup 4 mm
Viscosity :	(23 °C)		No data available	
Cinematic viscosity :	(40 °C)	>	20,5	mm ² /s
Solid content :			No data available	
Odour threshold :			not relevant	
Relative vapour density :	(20 °C)		No data available	
Vapourisation rate :			No data available	
Oxidising liquids :	Not oxidising.			

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated. Oxidizing agent.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

Acute effects

Acute oral toxicity

Parameter : ATEmix calculated
Exposure route : Oral
Effective dose : 12500 mg/kg
Parameter : LD50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Oral
Species : Rat
Effective dose : 1480 mg/kg
Parameter : LD50 (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Exposure route : Oral
Species : Rat
Effective dose : > 3000 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : 27500 mg/kg
Parameter : LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg
Parameter : LD50 (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 3000 mg/kg

Acute inhalation toxicity

Parameter : ATEmix calculated
Exposure route : Inhalation (vapour)
Effective dose : 215,7 mg/l
Parameter : LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 800 ppm
Exposure time : 8 h
Parameter : LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Mouse
Effective dose : 700 ppm
Parameter : LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 3,9 mg/l
Exposure time : 8 h

Irritant and corrosive effects

Irritation to respiratory tract

May cause respiratory irritation.

Practical experience/human evidence

The inhalation of dust/mist or aerosols causes irritation of the respiratory tract.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of skin contact

Frequently or prolonged contact with skin may cause dermal irritation.

SECTION 12: Ecological information

Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 1474 mg/l
Exposure time : 96 h
Parameter : LC50 (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Species : Fish
Effective dose : 9,2 mg/l
Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Brachydanio rerio (zebra-fish)
Effective dose : > 100 mg/l
Exposure time : 21 Days

Acute (short-term) daphnia toxicity

Parameter : EC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Daphnia magna (Big water flea)
Effective dose : 1550 mg/l
Exposure time : 48 h
Parameter : EC50 (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Species : Daphnia magna (Big water flea)
Effective dose : 3,2 mg/l
Exposure time : 48 h

Chronic (long-term) daphnia toxicity

Parameter : NOEC (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Daphnia magna (Big water flea)
Effective dose : 100 mg/l
Exposure time : 21 Days

Acute (short-term) algae toxicity

Parameter : EbC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Pseudokirchneriella subcapitata
Effective dose : 911 mg/l
Exposure time : 72 h
Parameter : ErC50 (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; CAS No. : 64742-95-6)
Species : Pseudokirchneriella subcapitata
Effective dose : 2,6 - 2,9 mg/l
Exposure time : 72 h

Bacteria toxicity

Parameter : EC0 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)
Species : Pseudomonas putida
Effective dose : > 700 mg/l
Exposure time : 16 h

12.2 Persistence and degradability

Biodegradation

The solvent is biodegradable. In accordance with the required stability the product is poorly biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

EWC-Code: 08 01 11. Uncleaned packaging: EWC-Code: 15 01 10. Cleaned packaging: EWC-Code: 15 01 04.

Waste treatment options

Appropriate disposal / Package

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

Note sections 7 and 8.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : 1 - 5 %

Water hazard class (WGK)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro-2K-PUR-Lack 5861 (SORTE 5861)
Revision date : 25.02.2020
Print date : 25.02.2020

Version (Revision) : 16.0.0 (15.0.0)

Class : 1 (Slightly hazardous to water) Classification according to AwSV

Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

15. Restrictions on use

16.2 Abbreviations and acronyms

TRGS: German Technical Rule for Hazardous Substances. BGR(I): Rule (Information) from the German employers liability insurance association. DGUV: German Statutory Accident Insurance. AwSV: Ordinance on plants for the handling of substances hazardous to water. VCI: German chemical industry association. EWC: European Waste Catalogue.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.