

Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier NT-Mischpulver EP/PE 5870 (SORTE 5870) 1.2 Polevant identified uses of the substance or mixture and uses advise

1.2 Relevant identified uses of the substance or mixture and uses advised against Powder coating. Intended purpose see technical data sheet.

Relevant identified uses

Products Category [PC]

Coatings and paints, thinners, paint removers

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor) Brillux GmbH & Co. KG, Industrielack www.brillux-industrielack.de

Street : Otto-Hahn-Straße 14

Postal code/city : D-59423 Unna

Telephone : +49 2303 8805-0

Telefax : +49 2303 8805-119

Information contact : E-mail address of the competent person for safety data sheets: sdb@brillux-industrielack.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english Telephone: +49 551 19 24 0 $\,$

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard statements

H412Harmful to aquatic life with long lasting effects.Precautionary statementsP260Do not breathe dust/fume/gas/mist/vapours/spray.P273Avoid release to the environment.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

 Tetradecyl-trimethyl-ammoniumbromid ; REACH No. : 01-2119989161-33 ; EC No. : 214-291-9; CAS No. : 1119-97-7

 Weight fraction :
 $\geq 0,025 - < 0,25 \%$

 Classification 1272/2008 [CLP] :
 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410 (M=10)



Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Change contaminated, saturated clothing. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO_2), water spray. The fire fighting for manuell and selfacting powder coating systems conformable BGI 764 the extingshent agent CO_2 can be used by movable tool and fight fire extingquishing system. For using other extingshent agent than CO_2 the effectiveness must be proved.

Unsuitable extinguishing media

Full water jet, inert gas with high pressure.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO₂) and pyrolysis products, toxic.

5.3 Advice for firefighters

Special protective equipment for firefighters Use suitable breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. See protective measures under point 7 and 8. Avoid dust formation. Do not inhale product dusts.

6.2 Environmental precautions

Page : 2 / 8



Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Take up dust-free and set down dust-free. Use approved industrial vacuum cleaner for removal. (Vacuum cleaner construction B1, appropriate to suck up combustible dust). Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Avoid: Generation/formation of dust, dust deposits, inhalation of dust/particles. Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Measures to prevent fire

Dust can form an explosive mixture with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Floors should be impervious and easy to clean.

Hints on joint storage

Storage class (TRGS 510): 11 Do not store together with Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

Further information on storage conditions

Do not store at temperatures above : 25 °C **Protect against :** Humidity.

7.3 Specific end use(s)

Powder coating. Intended purpose see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

Dust protection eye glasses Remark

Note DGUV-Rule 112-192.

Skin protection

Hand protection

Suitable gloves type : Disposable gloves. Gloves with long cuffs **Required properties** : dust-tight. antistatic.

Remark : After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.



Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

Body protection

Personel should wear protective clothings and all parts of the body should be washed after contact. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder is avoided.

Recommended material : Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Remark : Note DGUV-Rule 112-189. Note TRGS 401.

Respiratory protection

Respiratory protection necessary at: insufficient exhaust

Suitable respiratory protection apparatus

Use breathing filter P2 (particle).

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

General information

Used working clothes should not be worn outside the work area.

Other protection measures

Technical measures and the application of suitable work processes have priority over personal protection equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Powder (1-150 µm)

Colour : According to product identification.

Odour

Poor, characteristic.

Safety characteristics

Melting point/freezing point :		>	50	°C
Initial boiling point and boiling range :	(1013 hPa)		not applicable	
Decomposition temperature :		>	250	°C
Flash point : Auto-ignition temperature :		>	not applicable 450	°C
Lower explosion limit :		approx.	50 - 70	g/m ³
Lower explosion mint :			50 - 70	g/m
Upper explosion limit :			No data available	
Vapour pressure :	(50 °C)		not applicable	
Density :	(20 °C)		1,3 - 1,8	g/cm ³
Water solubility :	(20 °C)		practically insoluble	
рН :			No data available	
log P O/W :			not relevant	
Viscosity :	(23 °C)		not applicable	
Cinematic viscosity :	(40 °C)		not applicable	
Solid content :			100	Wt %
Odour threshold :			not relevant	
Relative vapour density :	(20 °C)		not applicable	
Vapourisation rate :			not applicable	
Flammable solids :	Not highly flammable.			
Oxidising solids :	Not oxidising.			

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).



Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

- No information available.
- **10.4 Conditions to avoid** No information available.

10.5 Incompatible materials No information available.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity	
Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 (Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2500 mg/kg
Acute dermal toxicity	
Parameter :	ATEmix calculated
Exposure route :	Dermal
Effective dose :	not relevant
Acute inhalation toxicity	
Parameter :	ATEmix calculated
Exposure route :	Inhalation (dust/mist)
Effective dose :	not relevant
Parameter :	ATEmix calculated (Tetradecyl-trimethyl-ammoniumbromid; CAS No.: 1119-97-7)
Exposure route :	Inhalation
Effective dose :	88 mg/l

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of skin contact

Powder coatings can cause localised skin irritation in folds of the skin or in contact with tight clothing.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity Parameter : Effective dose : Exposure time :

LC50 (Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7) 1,81 mg/l 96 h

Page : 5 / 8



Trade name :	NT-Mischpu	ver EP/PE 5870 (SORTE 5870)		
Revision date :	18.06.2020		Version (Revision) :	8.0.2 (8.0.1)
Print date :	23.06.2020			
Acuto (chort i	torm) toricity to			
Parameter :	term) toxicity to		l-ammoniumbromid ; CAS No. : 1119-97-7	7)
Effective dose	7 .	0,022 mg/l)
Exposure time		48 h		
•		aquatic algae and cyanob	acteria	
Parameter :	,,		l-ammoniumbromid ; CAS No. : 1119-97-7)
Effective dose	2:	0,0054 mg/l		,
Exposure time	e:	72 h		
12.2 Persistence a	and degradabi	lity		
Abiotic degr	-	•		
-		sewage plant is possible.		
Biodegradat				
-		ability the product is poorly b	iodegradable	
12.3 Bioaccumula		ability the product is poorly b	lodegradable.	
	•			
No information a				
12.4 Mobility in so				
No information a				
12.5 Results of PB				
The substances i	n the mixture do no	ot meet the PBT/vPvB criteria	according to REACH, annex XIII.	
12.6 Other advers	se effects			
No information a	vailable.			
12.7 Additional ec	otoxicologica	l information		
Additional info	-			
Do not allow un	ncontrolled discharg	e of product into the environ	ment.	
SECTION 13: Disp	oosal consider	ations		
13.1 Waste treatn	nent methode			
			t be carried out according to the EEC, s	pecific to the
		ste according to applicable le		
		aste Framework Dire		
Before intend	-			
		ions according to EWC/AV	rv	
	aste coating powde	_	•	
	I recommendatio			
•			inated packages in the same way as the	e substance itself.
13.2 Additional in				
Note sections 7 a				

Note sections 7 and 8.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards



Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 0.5 %

Water hazard class (WGK)

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

15. Restrictions on use

16.2 Abbreviations and acronyms

AwSV: Ordinance on plants for the handling of substances hazardous to water. BGR(I): Rule (Information) from the german employers liability insurance association. DGUV: German Statutory Accident Insurance. EWC: European Waste Catalogue. TRGS: German Technical Rule for Hazardous Substances. VCI: German chemical industry association.

16.3 Key literature references and sources for data

None

^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

	• •
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge.



Trade name : Revision date : Print date : NT-Mischpulver EP/PE 5870 (SORTE 5870) 18.06.2020 23.06.2020

Version (Revision) :

8.0.2 (8.0.1)

The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.