

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

NT-Mischpulver EP/PE 5872 (SORTE 5872)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Powder coating. Intended purpose see technical data sheet.

#### Relevant identified uses

##### Product Categories [PC]

PC9 - Coatings and paints, fillers, putties, thinners

#### Remark

The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co. KG, Industrielack  
www.brillux-industrielack.de

**Street :** Otto-Hahn-Straße 14

**Postal code/city :** D-59423 Unna

**Telephone :** +49 2303 8805-0

**Telefax :** +49 2303 8805-119

**Information contact :** E-mail address of the competent person for safety data sheets: [sdb@brillux-industrielack.de](mailto:sdb@brillux-industrielack.de)

### 1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english  
Telephone: +49 551 19 24 0

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; REACH registration No. : 01-2119453802-40 ; EC No. : 259-224-4; CAS No. : 54553-90-1

Weight fraction :  $\geq 1 - < 5\%$

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

Classification 1272/2008 [CLP] : Aquatic Chronic 3 ; H412  
Tetradecyl-trimethyl-ammoniumbromid ; REACH registration No. : 01-2119989161-33 ; EC No. : 214-291-9; CAS No. : 1119-97-7  
Weight fraction :  $\geq 0,025$  -  $< 0,25$  %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Change contaminated, saturated clothing. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

#### In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

#### After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), water spray. The fire fighting for manuell and self-acting powder coating systems conformable BGI 764 the extingshent agent CO<sub>2</sub> can be used by movable tool and fight fire extinguishing system. For using other extingshent agent than CO<sub>2</sub> the effectiveness must be proved.

#### Unsuitable extinguishing media

Full water jet, inert gas with high pressure.

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and pyrolysis products, toxic.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Use suitable breathing apparatus.

### 5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. See protective measures under point 7 and 8. Avoid dust formation. Do not inhale product dusts.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Take up dust-free and set down dust-free. Use approved industrial vacuum cleaner for removal. (Vacuum cleaner construction B1, appropriate to suck up combustible dust). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Avoid: Generation/formation of dust, dust deposits, inhalation of dust/particles. Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Measures to prevent fire

Dust can form an explosive mixture with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Floors should be impervious and easy to clean.

#### Hints on joint storage

Storage class (TRGS 510) : 11

#### Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

#### Further information on storage conditions

Do not store at temperatures above : 25 °C

Protect against : Humidity.

### 7.3 Specific end use(s)

Powder coating. Intended purpose see technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

GENERAL LIMIT VALUE FOR DUST

Limit value type (country of origin) : TRGS 900 ( D )

Parameter : A: respirable fraction

Limit value : 1,25 mg/m<sup>3</sup>

Peak limitation : 2(II)

Version : 29.03.2019

Limit value type (country of origin) : TRGS 900 ( D )

Parameter : E: inhalable fraction

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

Limit value : 10 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Version : 29.03.2019

## DNEL/DMEL and PNEC values

### DNEL/DMEL

Limit value type : DNEL worker (local and systemic) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Exposure route : Dermal  
Limit value : 0,792 mg/kg  
Limit value type : DNEL worker (local and systemic) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Exposure route : Inhalation  
Limit value : 0,697 mg/m<sup>3</sup>

### PNEC

Limit value type : PNEC (Aquatic, freshwater) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 0,009 mg/l  
Limit value type : PNEC (Aquatic, intermittent release) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 0,09 mg/l  
Limit value type : PNEC (Aquatic, marine water) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 0,0009 mg/l  
Limit value type : PNEC (Sediment, freshwater) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 0,0214 mg/kg  
Limit value type : PNEC (Sediment, marine water) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 0,00214 mg/kg  
Limit value type : PNEC (Soil) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 10 mg/kg  
Limit value type : PNEC (Sewage treatment plant) ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Limit value : 14 mg/l

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection

##### Suitable eye protection

Dust protection eye glasses

##### Remark

Note DGUV-Rule 112-192.

#### Skin protection

##### Hand protection

**Suitable gloves type** : Disposable gloves. Gloves with long cuffs

**Required properties** : dust-tight. antistatic.

**Remark** : After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note TRGS 401.

##### Body protection

Personel should wear protective clothings and all parts of the body should be washed after contact. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder is avoided.

**Recommended material** : Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

**Remark** : Note DGUV-Rule 112-189. Note TRGS 401.

#### Respiratory protection

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

Respiratory protection necessary at: insufficient exhaust

### Suitable respiratory protection apparatus

Use breathing filter P2 (particle).

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

### Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

### General health and safety measures

Used working clothes should not be worn outside the work area.

### Occupational exposure controls

#### Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state : Powder (1-150 µm)

Colour : According to product identification.

#### Odour

Poor, characteristic.

#### Safety relevant basis data

Melting point/melting range :	>	50 °C
Initial boiling point and boiling range :	( 1013 hPa )	not applicable
Decomposition temperature :	>	250 °C
Flash point :		not applicable
Ignition temperature :	>	450 °C
Lower explosion limit :	approx.	50 - 70 g/m <sup>3</sup>
Upper explosion limit :		No data available
Vapour pressure :	( 50 °C )	not applicable
Density :	( 20 °C )	1,4 - 1,8 g/cm <sup>3</sup>
Water solubility :	( 20 °C )	insoluble
pH :		No data available
log P O/W :		not relevant
Viscosity :	( 23 °C )	not applicable
Cinematic viscosity :	( 40 °C )	not applicable
Solid content :		100 Wt %
Odour threshold :		not relevant
Relative vapour density :	( 20 °C )	not applicable
Vapourisation rate :		not applicable
Flammable solids :		Not highly flammable.
Oxidising solids :		Not oxidising.

### 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

**Trade name :** NT-Mischpulver EP/PE 5872 (SORTE 5872)  
**Revision date :** 16.12.2019  
**Print date :** 16.12.2019

**Version (Revision) :** 7.0.1 (7.0.0)

### 10.3 Possibility of hazardous reactions

No information available.

### 10.4 Conditions to avoid

No information available.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )
Exposure route :	Oral
Species :	Rat
Effective dose :	7400 mg/kg
Parameter :	LD50 ( Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2500 mg/kg

##### Acute dermal toxicity

Parameter :	ATEmix calculated
Exposure route :	Dermal
Effective dose :	not relevant
Parameter :	LD50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg

##### Acute inhalation toxicity

Parameter :	ATEmix calculated
Exposure route :	Inhalation (dust/mist)
Effective dose :	not relevant
Parameter :	ATEmix calculated ( Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7 )
Exposure route :	Inhalation
Effective dose :	88 mg/l

### 11.3 Symptoms related to the physical, chemical and toxicological characteristics

#### In case of skin contact

Powder coatings can cause localised skin irritation in folds of the skin or in contact with tight clothing.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	EC50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )
-------------	---

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** NT-Mischpulver EP/PE 5872 (SORTE 5872)  
**Revision date :** 16.12.2019  
**Print date :** 16.12.2019

**Version (Revision) :** 7.0.1 (7.0.0)

Species : Brachydanio rerio (zebra-fish)  
Effective dose : > 1000 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7 )  
Effective dose : 1,81 mg/l  
Exposure time : 96 h

#### Acute (short-term) daphnia toxicity

Parameter : EC50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 125 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7 )  
Effective dose : 0,022 mg/l  
Exposure time : 48 h

#### Acute (short-term) algae toxicity

Parameter : EC50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Species : Desmodesmus subspicatus  
Effective dose : 9 mg/l  
Exposure time : 72 h  
Parameter : EL50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Species : Scenedesmus subspicatus  
Effective dose : 0,64 mg/l  
Exposure time : 72 h  
Parameter : IC50 ( Tetradecyl-trimethyl-ammoniumbromid ; CAS No. : 1119-97-7 )  
Effective dose : 0,0054 mg/l  
Exposure time : 72 h

#### Bacteria toxicity

Parameter : EC50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Species : Bacteria toxicity  
Effective dose : 140 mg/l  
Exposure time : 17 h  
Parameter : EC50 ( benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) ; CAS No. : 54553-90-1 )  
Species : Bacteria toxicity  
Effective dose : 125 mg/l  
Exposure time : 96 h

## 12.2 Persistence and degradability

### Abiotic degradation

Mechanical separation in a suitable sewage plant is possible.

### Biodegradation

In accordance with the required stability the product is poorly biodegradable.

## 12.3 Bioaccumulative potential

No information available.

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

## Additional information

Do not allow uncontrolled discharge of product into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose according to legislation.

#### Product/Packaging disposal

**Waste codes/waste designations according to EWC/AVV**

##### Waste code product

EWC-Code: 08 02 01.

##### Waste treatment options

##### Appropriate disposal / Package

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### 13.2 Additional information

Note sections 7 and 8.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Other regulations (EU)

##### Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### National regulations

##### Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 0,5 %

##### Water hazard class (WGK)

Class : 2 (Significant hazardous to water) Classification according to AwSV

##### Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : NT-Mischpulver EP/PE 5872 (SORTE 5872)  
Revision date : 16.12.2019  
Print date : 16.12.2019

Version (Revision) : 7.0.1 (7.0.0)

## 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

15. Restrictions on use · 15. Water hazard class (WGK)

### 16.2 Abbreviations and acronyms

TRGS: German Technical Rule for Hazardous Substances. BGR(I): Rule (Information) from the German employers liability insurance association. DGUV: German Statutory Accident Insurance. AwSV: Ordinance on plants for the handling of substances hazardous to water. VCI: German chemical industry association. EWC: European Waste Catalogue.

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### 16.6 Training advice

None

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.