

Technical Data Sheet

PUR Thinner 5102



Medium volatile, colorless

Field of application

Special thinner with medium volatility. Mainly recommended for spray application methods.
Due to the high thinning capacity, make sure that, in the case of multi-layer coating systems, only so-called nitro-resistant prime coats are used in order to avoid the risk of stripping and lifting.

Properties

- medium volatile
- high thinning capacity

Technical data

Basis	Aromatic hydrocarbons, esters
Colors	colorless
Density	0.88 to 0.92 g/cm ³ (in accordance with DIN EN ISO 2811)
Flash point	> 23 °C
Labeling	See current safety data sheet.

Packaging

1 l, 5 l, 30 l, 200 l

Shelf life

24 months after receipt of the goods in the original sealed container.
Store in a sealed container in a dry place and at room temperature (at most 25 °C). Protect from heat sources and direct sunlight.

Minimum shelf life refer to label

Remark

This Technical Data Sheet is based on intense development work and many years of practical experience. The contents do not constitute any contractual relationship. The user/buyer is not released from his/her obligation to test our products for suitability for the intended application. In addition, our General Terms and Conditions shall apply.

As soon as a new edition of this Technical Data Sheet is issued, the previous specifications become invalid.

If you need the current version, please contact your Brillux consultant, Version 4.

Brillux GmbH & Co. KG Industrielack
Otto-Hahn-Straße 14
59423 Unna
Tel. +49 2303 8805-0
Fax +49 2303 8805-119
info@brillux-industrielack.de
www.brillux-industrielack.de