

## PUR Thinner 5103

High volatile, colorless

### Basis

Esters

### Color

Colorless

### Properties

- high volatile
- aromatics-free, mild smelling
- high thinning capacity
- compared with PUR Thinner 5102 PUR Thinner 5103 has a higher volatility

### Field of application

Special thinner with high volatility. Mainly recommended for spray application methods. Due to the high thinning capacity, make sure that, in the case of multi-layer coating systems, only so-called nitro-resistant prime coats are used in order to avoid the risk of stripping and lifting.

### Technical data

#### Density

0.87 to 0.89 g/cm<sup>3</sup>  
(in accordance with  
DIN EN ISO 2811)

#### Flash point

>23 °C

#### Labelling

See current safety data sheet.

#### Packaging

1 l, 5 l, 30 l, 200 l

#### Storage

1 year after receipt.  
Store in original closed  
container, dry and at room  
temperature. Protect against  
heat and direct sun impact.

### Remark

This Technical Data Sheet is based on intense development work and many years of practical experience. The contents do not constitute any contractual relationship. The user/buyer is not released from his/her obligation to test our products for suitability for the intended application. In addition, our General Terms and Conditions shall apply. As soon as a new edition of this Technical Data Sheet is issued, the previous specifications become invalid. If you need the current version, please contact your Brillux consultant.  
Version 1

Brillux Industrial Coatings  
Otto-Hahn-Str. 14  
59423 Unna  
Germany  
Phone +49 (0)2303 8805-0  
Fax +49 (0)2303 8805-119  
[www.brillux-industrial-coatings.com](http://www.brillux-industrial-coatings.com)  
[info@brillux-industrial-coatings.com](mailto:info@brillux-industrial-coatings.com)