

# Technical Data Sheet

## Demi-Water 5110



**Desalinated water with low conductivity**

### Field of application

Rinsing and cleaning water, thinning for water-dilutable coating materials.

### Properties

- Desalinated water with low conductivity

### Material description

<b>Basis</b>	Fully desalinated water
<b>Color shades</b>	Colorless
<b>Density</b>	1.0 g/cm <sup>3</sup> (in accordance with DIN EN ISO 2811)
<b>Flash point</b>	Not applicable
<b>Labeling</b>	See current Safety Data Sheet.

### Container sizes

10 l, 200 l

### Shelf life

24 months after receipt of goods.  
Store in a sealed container in a dry place and at room temperature (max. 25°C). Protect from heat sources and direct sunlight.

**Minimum shelf life** Refer to label

This Technical Data Sheet is based on extensive development work and years of practical experience. The content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.

Upon publication of a new version of this information sheet as a result of new technical developments, all of the information provided above becomes invalid. You can obtain the latest version from your Brillux consultant or at [www.brillux-industrielack.de](http://www.brillux-industrielack.de), version 3, as required.

Brillux GmbH & Co. KG Industrial Coatings  
Otto-Hahn-Straße 14  
59423 Unna  
Tel. +49 2303 8805-0  
Fax +49 2303 8805-119  
[info@brillux-industrielack.de](mailto:info@brillux-industrielack.de)  
[www.brillux-industrielack.de](http://www.brillux-industrielack.de)

