

Drawing and Punching Compound 5115.-.0137

Medium volatility, low aromatics content, for medium to heavy-duty deformation of steel sheets

Basis

Organic solvent with paint friendly ingredients

Color

Colorless

Properties

- organic solvent, low aromatics
- mild odor
- can be painted immediately once the solvent has evaporated

Field of application

This Drawing and Punching Compound is suitable for medium to heavy-duty deformation of steel sheets.

Technical data

Density

0.75 to 0.77 g/cm³
(in accordance with DIN EN ISO 2811)

Flash point

> 23 °C

Labelling

See current safety data sheet.

Application

Spraying, roller coating application, curtain coating

Packaging

200 l

Storage

1 year after receipt.
Store in original closed container, dry and at room temperature. Protect against heat and direct sunlight.

Remark

This Technical Data Sheet is based on intense development work and many years of practical experience. The contents do not constitute any contractual relationship. The user/buyer is not released from his/her obligation to test our products for suitability for the intended application. In addition, our General Terms and Conditions shall apply. As soon as a new edition of this Technical Data Sheet is issued, the previous specifications become invalid. If you need the current version, please contact your Brillux consultant.
Version 3

Brillux Industrial Coatings
Otto-Hahn-Strasse. 14
59423 Unna
Germany
Phone +49 (0)2303 8805-0
Fax +49 (0)2303 8805-119
www.brillux-industrial-coatings.com
info@brillux-industrial-coatings.com